

AEGIS

8000P SERIES

MULTI TENANT REMOTE PROGRAMMABLE



- 250 tenants and 250 access codes.
- Programming: Remote Software Via Dial-up Modem or Local Via Keypad
- Non-Volatile Memory
- Backlit Keypad Button
- Event recording with 600 events buffer
- 1x16 Liquid Crystal Display (LCD)
- Two relays • Support pause dialing from PBX
- Indoor or outdoor, surface and full-flush mount.
- Brushed Stainless Steel Faceplate

Warranty: 24 month

Purchase UPS2L, will include lightning on 24 months warranty

SPECIFICATIONS

POWER INPUT: 12VAC/40VA (supplied) or 12-VDC/40VA with battery backup charging circuit.

CURRENT CONSUMPTION: 500mA idle, 800mA operating.

OPERATING ENVIRONMENT: 32°F to 140°F. *Heater is required if the temperature is below 32°F.*

NIGHT LIGHT: Super Bright Light Emitting Diode (LED).

CONSTRUCTION: 16 Gauge Cold Rolled Steel back box with enamel finished and Brushed Stainless Steel Faceplate

MOUNTING: Surface and full-flush.

DIMENSIONS:

Surface 10-13/16 "(H) x 8-5/8 "(W) x 3-3/4 "(D).

Full-flush 10-13/16"(H) x 8-3/8"(W) x 2-7/16(D)

MOUNTING RING FULL-FLUSH (FFM7 is included):

Inside 11-1/8" (H) x 8-11/16"(W) x 2-5/8"(D)

Outside 14-5/16" (H) x 12-1/8" (W)

SHIPPING WEIGHT: 10-12 lbs approximate.

ORDERING PART

Surface Mount

8250P

250 tenants 250 access codes

Full-flush Mount

8250FFP

250 tenants 250 access codes

ACCESSORIES

Radio Receiver and Transmitter

ARFR Radio Frequency Receiver

ARFT Radio Frequency Transmitter

ARFHT Radio Frequency Handheld Transmitter

Video Package

UVPC Color Camera Package

UVPB Video Balun for Twisted Pair video transmission

Pedestal Mounting Post, Adapter Plate and Mounting Ring

UPM1S Standard Single Arm (42"H, 5"x5" base)

UPM4S Standard Single Arm (47"H, 5"x5" base)

UPM1L Large Single Arm (47"H, 8"x8" base)

UPM6L Large Single Arm (64"H, 8"x8" base)

UPM8L Large Single Arm (84"H, 8"x8" base)

UPM2 Double Vertical Arm (44"/84"H, 8"x8" base)

UPM5 Double Horizontal Arm (47"H, 8"x8" base)

UPMDB64 Single Arm Direct Buriel (64"H)

UPMDB72 Single Arm Direct Buriel (72"H)

UAP78 Adapter Plate AeGIS 8000P Series

UPM12E 12" Expansion Arm use for all UPM

Miscellaneous Accessories

USP1 AC and Telephone Surge Protector.

USP2L Surge and Lightning Protection, *include Lightning on 24 months warranty*

AHP5 Heater Pad with Thermostat.

UBAT1 12VDC 4.5 Ahr backup battery.

UXIT Multipurpose push button switch

Specifications subject to change without prior notice

PACHCO

Since 1978

Home of Telephone Entry Access Control Systems

San Clemente, California

1-888-678-7224

www.pach-co.com