







FOTA – Upgrade firmware via SMS.



Ability to view APN on signal level reply.



Bigger 2 amp power supply.



Trigger, latch and unlatch SMS replies added. Ability to disable.







Store up to 4 notification phone numbers to receive an SMS (customizable) when relay is triggered etc



Add up to 250 time restricted caller ID numbers.



Prox (RFID) option.



Ability to check Do Not Disturb Times.



0 0 0

3rd Gen surge protection.



Dual network



T··Mobile·



NEW AES PRO APP, user friendly. With Installer and homeowner capabilities.

		Technical Details	
Dial Out Numbers	4	Relays	2
Permanent Codes/cards	250	Relay Type	N/C and N/O
Time Restricted Codes/cards	250	Relay Load	2 amps, 24v ac max
Temporary Codes/cards	50	Power Consumption	300mA on dial out, 2amp peak demand
Automatic Trigger Events per Week	50	Modem Models	4G USA
Caller ID Numbers	250	Power Supply	24v dc (24v 2A dc adaptor included)
Time Restricted Caller ID Numbers	250		



Pedestal Panels



Pedestal panel with keypad, constructed from marine grade stainless steel, powder coated aluminium hood and gloss black toughened acrylic faceplate.


Non-Keypad panel: PRIME7-PB-US



PRIME7-PSK-US

All stainless, marine grade steel pedestal mount cellular intercom. Illuminated call button & keypad. Complete with power supply & built in antenna.


NON Keypad panel: PRIME7-PS-US



Architectural

PRIME7-AB-US

Stylish curved architectural model. Constructed from BS316 marine grade stainless steel and finished with gloss black acrylic trim. Blue backlighting.





PRIME7-ABK-US

Stylish curved architectural keypad model. Constructed from BS316 marine grade stainless steel and finished with gloss black acrylic trim. Blue backlighting.

