

Specifications

Image Sensor	1 / 2.7" CMOS
Resolution	2560 (H) x 1920 (V)
Effective Pixels	5 Mega Pixel
Focal Length	3.6mm
IR Distance	Up to 75 ft. / 18 pcs.
Output Mode	AHD / CVI / TVI / Analog
Min. Illumination	Color: 0.1 Lux White/Black: 0.1 Lux (with IR LED on)
AGC	Auto
WB	Auto
AES	NTSC: 1/60s-1/10000s PAL: 1/50s-10000s
D/N Switch	Color/WB/IR (outside) / inside auto
Contrast	10 Level can be adjusted
Sharpness	20 Level can be adjusted
Saturation	20 Level can be adjusted
DNR	15 Level can be adjusted
Video System	NTSC
DWDR	OFF/ON
S/N Ratio	More than 48dB
Storage Temp.	-40°C ~ 60°C
Operating Temp.	-40°C ~ 55°C
Power Supply	DC12V
Weight (with bracket)	0.8 lbs


Highlights

- Coax Control
- AHD / CVI / TVI / ANALOG 4 in 1
- 5MP @ 30fps
- 3.6mm lens
- 18 pcs. SMD LED
- IR Distance: Up to 75 ft.
- Weather-rating: IP66

OSD menu: change mode

