DESCRIPTION




The **DP28NIT** is the basic Door Station model. Manufactured in a sturdy ivory polymer, this Door Stations look great anywhere it is placed. This unit provides standard door-to-phone communication when used with the **DP28C***. Installation and operation are very simple. The **DP28NIT** is also available in a kit with the DP28C as the **DP28IT**.

*DP28C only included in kits

DP28NITIvory Polymer

FEATURES

- Manufactured in sturdy polymer
- Elegant Ivory finish looks great on any surface
- Mounts easily on most surfaces including stucco, fences, and gates
- Installs with a single pair of wires
- Optional Door Station Awning (DP28NTA) for additional style as well as protection from the environment
- No external power required: power drawn from connected Main Door Station Controller



APPLICATIONS

- Communicate with people at a door, gate, or any other entrance way where Door Station is present
- Use in conjunction with the DP29CI to activate external trigger devices (e.g. door chimes, cameras, lights...) with the Door Station
- Use in conjunction with the DP29SW to open electronically locked doors or gates with the phone
- Use as extra Door Station to any Door Station Kit

SPECIFICATIONS

Power:

N/A

Dimensions:

• 3.875" x 5.125" x 1.25"

Shipping Weight:

• 1.0 lbs

Speaker:

• Frequency Response: 400~2.8kHz

Impedance: 8ΩPeak Power: 0.25W

Microphone:

• Frequency Response: 200~6.8kHz

