

ULTRALOOP® - ULT-DIN

VEHICLE LOOP DETECTOR

The ULTRALOOP® series vehicle loop detector combines small size with full-featured functionality in a DIN rail mount module.

- Sensitivity display - easy set up and installation by selecting the correct sensitivity
- Cross Talk and RFI interference display - easy identification of interference problems
- Small size - fits in to small operator housings and saving space (80 x 23 x 84mm)
- 10 sensitivity settings - gives the user the ability to select the best sensitivity level
- Low current draw - green product
- **DETECT-ON-STOP™** or (DOS®) feature will allow detection only when a vehicle has come to a complete stop on the loop. This EMX exclusive feature is a major advantage if you want to ignore cross traffic in tight spaces.

The ULT-DIN provides relay contact outputs indicating vehicle presence, and a second set of contacts that may be used for loop fault, pulse on entry /pulse on exit, or Detect-On-Stop™ (DOS®). The ULT-DIN features automatic sensitivity boost (ASB), delay, fail-safe/fail-secure and infinite or normal (5 min.) presence.

The ULTRALOOP® is easily installed and has user-friendly features that simplify set-up, operation and troubleshooting. Sensitivity selection is simplified by the ULTRAMETER™ display that indicates the appropriate sensitivity setting the vehicle positioned on the loop. The 10 sensitivity settings allow for finer adjustment of the detection level, while the 4 frequency selections provide greater flexibility in preventing crosstalk in multi-loop applications.

ULT-DIN



Features

- Presence output
- Output B
- Pulse entry/exit
- Detect-On-Stop™
- ASB (Automatic Sensitivity Boost)
- Delay
- Normal/infinite presence
- Loop fault output

Connections

LOOP
Loop
Shield
+V (12 to 24VAC/VDC)
-V (power supply common or VAC)
Presence - Relay 1 NC contact
Presence - Relay 1 common contact
Presence - Relay 1 NO contact
Output B - Relay common contact
Output B - Relay NO contact



PR-XX



ULT-DIN

Technical Data

Sensitivity	10 levels, 0-9
ULTRAMETER™ Display	Indicates optimum sensitivity level, 0-9 Diagnostic aid
Loop Frequency	4 settings (low, med-low, med-hi, high)
Loop Inductance	20...2000µH (Q factor > 5)
Grounded Loop	Isolation transformer allows operation with poor quality loops
Automatic Tuning	Detector tunes to loop on power-up and following frequency count function
Environmental Tracking	Automatic compensation
Surge Protection	Loop circuitry protected by surge suppressors
Presence Relay	SPDT relay contacts (form C)
Output B Relay	SPST relay contact (form A)
Contact Ratings	1A @ 24VDC...120VAC
Power / Loop Fault Indicator	Green LED
Detect / Frequency Count Indicator	Red LED
Detect-On-Stop™	Requires vehicle to stop for a minimum of 1 second (1-2s typical)
ASB (Automatic Sensitivity Boost)	Increases sensitivity after initial detection to prevent dropout due to high-bed vehicles
Power	12VDC...24VDC, 24VAC
Operating Current	15mA standby / 45mA detect
Operating Temperature	-40°C...82°C (-40°F...180°F) 0...95% relative humidity
Dimensions (L x W x H)	80mm (3.2") x 23mm (0.9") x 84mm (3.3")
Weight	0.25 lbs. (113 g)
Mounting Method	DIN rail mount - 35mm width
Connections	10 screw terminals

Ordering Information

- ULT-DIN Ultra DIN Vehicle loop detector, dual output, DIN rail mount
- PR-XX EMX Lite Preformed Loop (XX- specify size)



WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of sale to our customer. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship. Rev 1.6 02/17/2020

