









SMART-81S is a next generation retransfer card printer that offers the industry's fastest first-card-out speed. IDP's innovative retransfer heating technology-Rapid Retransfer Printing technology or "RRP" provides the fastest "Ready to Print" metric in the industry. No more waiting several minutes for your outdated retransfer printer to heat up.

RRP technology from IDP offers power-on and Ready to Print in only seconds. The SMART-81S produces higher quality, sharper-looking images than traditional card printers. It is the perfect choice for demanding applications that require deep dark colors with infinity-edge (full-bleed) graphics on blank or technology cards.

The input card hopper holds up to 200 cards and physical security features allow you to secure your printer, its supplies, and ejected cards in instant bank card issuance or high-security applications.

### **Features**

- The FASTEST First-Card Out speed
- High Volume Capacity (200 cards)
- Infinity Edge / Over the Edge Printing
- Stress-free Anti-dust circulation
- Advanced Bank Card Issuance Security
- Robust & Innovative Product design







## Issuance

SMART IDesigner ensures accurate card issuance and data management with your SMART series of printers. This application offers simple design tools to allow the user to create a truly customized card within minutes. SMART IDesigner offers advanced user tools such as database connections, camera and signature scanners, plug-in support, as well as smart card reading and encoding.

- Design and print (Image, Photo, and Text)
- 1D & 2D Barcode printing
- Auto portrait (Auto face detection, adjustment of size & position)
- Printing of sequential numbers
- Card design templates
- Plug-in for supporting external devices (Sign pad, Camera, Scanner)
- Convenient card issuance and data management
- Magnetic stripe (MS), contact & contactless smart card encoding by using a plug-in program



The SMART series printers come with highly effective and tested physical and electronic security features.

- PASSWORD verification with administrator and user authentications
- PC AUTHENTICATION locks the SMART printer to a specific PC to render it useless if stolen
- DATA ENCRYPTION over USB and SSL (secure socket layer) over Ethernet
- PHYSICAL LOCKS are standard on the SMART-70 and an optional feature on the SMART-51 Series
- Ethernet SNMPv3



# Networking

The SMART series offers "single-wire" printing and encoding.

- The SMART Ethernet module can not only print over your network, but can also be configured to encode a magnetic stripe, contact IC chips, and contactless smart cards over your
- The SMART Ethernet module can be configured to accept "open. card protocol" print commands for direct printing without a driver

#### **Printing**

| Print Type | Retransfer Dye-Sublimation / Resin Thermal |
|------------|--------------------------------------------|
| Print Area | Single-Sided                               |
| Resolution | 300dpi                                     |

#### **Print Speed**

| YMCK   | Max. 25 sec./card (144 cards/hour)    |
|--------|---------------------------------------|
| YIVIUN | IVIAX. 25 Sec./Cald (144 CaldS/110ul) |
|        |                                       |

#### **System**

| Display | 2 Line Graphic LCD Indicator | / 4 Buttons |
|---------|------------------------------|-------------|
|         |                              |             |

Microsoft Windows 2000/2003/XP/Vista/7/8/10/11, Supported Platforms

Mac OS, Linux

Communication USB, & Ethernet

Power Supply 100-240V~50/60Hz 2.5A Temperature/Humidity 15~35ºC/35~70%

#### **Certifications**

CB CE FC IS C

### Card

| Card Feeding   | Automatic                            |
|----------------|--------------------------------------|
| Card Size      | ISO CR80 (54mm x 86mm/2.12" x 3.38") |
| Card Thickness | 0.76mm (30mil) ~ 1.6mm (64mil)       |
| Card Type      | PVC, PET, Composite PVC              |
|                |                                      |

#### Capacity

| Input Hopper  | 200 Cards |
|---------------|-----------|
| Output Hopper | 100 Cards |

#### **Dimensions**

| Millimeter (WxDxH) | 460 x 224 x 310 |
|--------------------|-----------------|
| Inch (WxDxH)       | 181 x 88 x 12 2 |

### Weight

Kg/lbs 11.4/25.13

#### **Encoding Options**

| Magnetic I | ISO 7811 (Track I, II, III Read/ Write, HiCo/ LoCo) |
|------------|-----------------------------------------------------|
|------------|-----------------------------------------------------|

Contact ISO 7816 (ID-1)

ISO 14443 (Type A/B), ISO 18092(NFC), MIFARE, Contactless

**DESFIRE** 

Security Physical & Electronic Locking System

#### **Consumables**



Color Ribbons

Full Color Ribbon with Resin Black

Full Color Ribbon with Resin Black & Resin Black for Back Side

500 Cards/Roll

500 Cards/Roll



Retransfer Film

500 Cards/Roll



Ribbon & Film Package

Full Color Ribbon with Resin Black & Retransfer Film

500 Cards/Roll



460mm (18.1 inch)

# **IDP Americas, Inc.**

1485 South County Trail - Unit 306, East Greenwich, RI 02818 TEL +1.401.400.7111 FAX +1.401.667.7445 E-MAIL sales@idpamericas.com

### IDP Corp., Ltd.

#601, 50, Digital-ro 33-gil, Guro-gu, Seoul, Korea, 08377 TEL +82.2.6099.3700 FAX +82.2.6099.3717 E-MAIL sales@idp-corp.com

SMART-81S 653636 **SMART-81SS** 653638 Contactless Enc. (USB) 653540 **Contact IC Enc.** 653539 **Mag Encoding** 653538 YMCK & Retransfer Film Pack 653547 YMCK (no film included) 659896 YMCKK (no film included) 653378 653431 **Retransfer INTM Film** Clear 1mil Laminate Film 653629 Celestial Hologram 1 mil Film 653630 Clear IC Chip, 1mil Film 653631

310mm (12.2 inch)

Add "K" to any printer part number for a kit (1 YMCKO Ribbon, 1-100pk Cards, & 1 Long Cleaning Card)