

This all-purpose flashlight is designed for the broadest range of lighting needs at the best value. Now producing 425 lumens for three hours!



Four operating modes:

- High for a high lumen, far-reaching beam: 425 lumens; 26,000 candela; 322m beam; runs 3 hours
- Medium for bright light and longer run time: 200 lumens; 12,000 candela; 219m beam; runs 5.5 hours
- Low provides a less intense beam and extended run time: 100 lumens; 6,000 candela; 155m beam; runs 10 hours
- Strobe for disorienting or signaling: runs 7.5 hours

Optimized electronics provide regulated intensity

IPX4 water resistant; 1m impact resistance tested

Serialized for positive identification

Stinger LED: 8.41" (21.36 cm); 12.4 oz. (352 g)  
 Stinger DS LED: 8.85" (22.48 cm); 12.8 oz. (364 g)

Limited Lifetime Warranty  
 Visit [www.streamlight.com](http://www.streamlight.com) for full warranty information

See reverse for system configurations

<b>PART NBR</b>	<b>ITEM DESCRIPTION</b>
<b>STINGER LED</b>	
75962	STINGER LED - 230V AC/12V DC - 2 HOLDERS
75729	STINGER LED - 240V AC/12V DC - 2 HOLDERS
75718	STINGER LED - 100V AC/12V DC - 2 HOLDERS
75713	STINGER LED - 120V AC/12V DC SMART CHARGE - 2 HOLDERS
75711	STINGER LED - 120V AC SMART CHARGE
75712	STINGER LED - 12V DC SMART CHARGE
75732	STINGER LED - 120V/100V AC/12V DC PIGGYBACK SMART CHARGE
75710	STINGER LED - (WITHOUT CHARGER)
<b>STINGER DS LED</b>	
75972	STINGER DS LED - 230V AC/12V DC - 2 HOLDERS
75829	STINGER DS LED - 240V AC/12V DC - 2 HOLDERS
75818	STINGER DS LED - 100V AC/12V DC - 2 HOLDERS
75813	STINGER DS LED - 120V AC/12V DC SMART CHARGE - 2 HOLDERS
75866	STINGER DS LED- 120V AC/12V DC 1 HOLDER SMART CHARGE - CLAM
75811	STINGER DS LED - 120V AC SMART CHARGE
75812	STINGER DS LED - 12V DC SMART CHARGE
75832	STINGER DS LED - 120V/100V AC/12V DC SMART CHARGE PIGGYBACK
75810	STINGER DS LED (WITHOUT CHARGER)

