



**Materials:**

- Low Carbon Steel ( $F_y = 32,000$  psi minimum,  $F_t = 52,000$  psi minimum)

**Finishes:**

- **Electrogalvanized (EG):**  
Conforms to ASTM B633, Type III SC1
- **Unistrut Defender (DF):**  
Conforms to ASTM A1059

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 316 (SS):** ASTM A240, Type 316 \*

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	Thread Size	Length (ft)	Finish	Product Weight / Ft (lbs/ft)
HTHR025	1/4"	10'	EG	0.12
HTHR025	1/4"	12'	EG	0.12
HTHR037	3/8"	10'	EG	0.29
HTHR037	3/8"	12'	EG	0.29
HTHR037	3/8"	6'	DF	0.29
HTHR050	1/2"	10'	EG	0.53
HTHR050	1/2"	12'	EG	0.53
HTHR050	1/2"	6'	DF	0.53
HTHR062	5/8"	10'	EG	0.84
HTHR075	3/4"	10'	EG	1.24

<b>Project:</b>	<input style="width: 90%;" type="text"/>		
<b>Architect / Engineer:</b>	<input style="width: 90%;" type="text"/>		
<b>Date:</b>	<input style="width: 15%;" type="text"/>	<b>Phone:</b>	<input style="width: 25%;" type="text"/>
<b>Contractor:</b>	<input style="width: 90%;" type="text"/>		
<b>Address:</b>	<input style="width: 90%;" type="text"/>		
<b>Notes:</b>	<input style="width: 90%;" type="text"/>		

**Approval Stamp:**