



**Materials:**

- Unistrut Channel Nuts are manufactured from mild steel cold rolled coil, and after stamping and machining operations are completed, they are case hardened, assuring positive biting action into the inturned edge of the Unistrut Channel.
- **1/4" & 5/16" Sizes:** Conforms to ASTM A1011 SS GR 33
- **3/8", 7/16" & 1/2" Sizes:** Conforms to ASTM A576 GR 1015 Modified
- **5/8", 3/4" & 7/8" Sizes:** Conforms to ASTM A36 or A675 GR 60

**Finishes:**

- **Electrogalvanized (EG):** Conforms to ASTM B633, Type III SC3
- **Unistrut Defender (DF):** Conforms to ASTM A1059
- **Hot Dip Galvanized (HG):** Conforms to ASTM A153

**Materials & Finishes - Special Metals:**

- **Stainless Steel, Type 316 (SS):** ASTM A240, Type 316 \*
- **Aluminum (AL):** Stainless Steel nuts are recommended for Aluminum channel.

\* These materials have different physical properties and performance characteristics. Please [contact us](#) for design support.

Part No.	Thread Size	Finish	Product Weight / Piece (lbs)
P1006-0832	#8-32	EG	0.07
P1006-1024	#10-24	EG	0.07
P1006-1024	#10-24	SS	0.07
P1006-1032	#10-32	EG	0.07
P1006-1420	1/4"-20	EG	0.07
P1006-1420	1/4"-20	DF	0.08
P1006-1420	1/4"-20	HG	0.08
P1006M6	M6	EG	0.07
P1006M6	M6	SS	0.07
P1006U1420	1/4"-20	SS	0.07
P1007	5/16"-18	EG	0.06
P1007	5/16"-18	HG	0.07
P1007	5/16"-18	SS	0.06
P1007M8	M8	EG	0.07
P1007M8	M8	SS	0.07
P1008	3/8"-16	EG	0.1
P1008	3/8"-16	DF	0.11
P1008	3/8"-16	HG	0.11
P1008M10	M10	EG	0.11
P1008M10	M10	SS	0.11
P1008U	3/8"-16	SS	0.1
P1009	7/16"-14	EG	0.09
P1010	1/2"-13	EG	0.12
P1010	1/2"-13	DF	0.13
P1010	1/2"-13	HG	0.13
P1010M12	M12	EG	0.13
P1010M12	M12	SS	0.13
P1010U	1/2"-13	SS	0.11

Project:

Architect

**/ Engineer:**

**Date:**

**Phone:**

**Contractor:**

**Address:**

**Notes:**

**Approval Stamp:**