

Specifications

Image Sensor	1 / 2.8" CMOS
Resolution	1920 (H) x 1080 (V)
Effective Pixels	2 Mega Pixel
Video Format	PAL/NTSC
Min. Illumination	Color: 0.05 Lux @F1.6 B/W:0.005Lux @F1.6
Video Output	AHDH (1Vp-p 75 ohm)
S/N Ratio	50dB
White Balance	Auto
Day & Night	IR-CUT

Functions

IR Control	Changing focus proportion w/lens zoom
IR Range	Up to 500 ft.
Pan Range	Pan: 0°~360° Continuous Tilt: -15°~90°
Speed	PTZ: Horizontal 0.1°~240°/sec Vertical: 0.1°~240°/sec
Preset	255
Patrol	4 Groups, each group: 10 presets
Auto Scan	1
360° Pan Scan	1
Home	Preset / Patrol / Area Scan / Pan Scan

Lens

Focal Length	4.7 to 84.6mm (F1.6 to F2.7)
Optical Zoom	36X Optical Zoom

General

Power Supply	DC12VA
Power Consumption	12W
Operating Temp.	-40°C~60°C; RH<90%
Protection Level	4000Surge Protection
Weather-Rating	IP66
Material	Metal-Cast Aluminum
Size	185.0 mm X 375 mm
Weight	4.3kg (including packaging)
Accessories	Wall-Mount bracket, power

Input / Output

Analog Output	1.0Vpp/75, NTSC or PAL, BNC Connector
Communication	Pelco Coaxitron over Coaxial Cable



Highlights

- Coax Control
- IR LEDs 4 pcs.
- IR Range: Up to 500 ft.
- IR Mode: Auto, All On, All Off
- 360° Continuous rotation
- Maximum 255 preset positions
- 4 patrol groups
- Weather-Rating IP66