

## FEATURES

- TRANSFER 60Mbps BI-DIRECTIONAL ETHERNET SIGNAL VIA COAXIAL CABLE
- TRANSMISSION DISTANCE SIGNALS UP TO 1000 FEET
- LOW RATE DELAY, LESS THAN 20US
- PLUG & PLAY
- BUILT-IN SPLICING SLOT, WITH MAGNET AND HANGER
- UNIQUE AND INTEGRATED DESIGN
- DESKTOP & WALL MOUNTED INSTALLS AVAILABLE



Bolide's new BE8216EOC/POE1000 Ethernet Extender can transfer Ethernet signal and power by Ethernet cable or coaxial cable. It consists of SV and IPC pieces. This product is specially designed to meet the power supply in the long-distance HD IP transmission and accord with IEEE 802.3af and IEEE 802.3at standard. This device can transfer the Ethernet signal and power up to 1000ft. through the coaxial cable. Network latency is less than 20us. The structure design of built-in splicing slot on both sides with magnetic attraction enables multiple installation methods. This is a cost effective choice for the HD network surveillance system.

## CONNECTOR

<b>Port</b>	BNC, RJ45
<b>Transmission Distance</b>	EOC coaxial cable; 0-100m Coaxial Cable: 0-1000ft (recommended)
<b>Transmission Media</b>	RG59 or above coaxial cable and Cat5e/6 cable

## NETWORK

<b>Network Standard</b>	IEEE 802.3u 100BASE-TX
-------------------------	------------------------

## STATUS INDICATION

<b>Power Indication</b>	Yellow lasting on: Power connection OK
<b>Data Indication</b>	Green lasting on: Data connection is OK
<b>RJ45 Indication</b>	Green flicker: Data transmission is OK Yellow flicker: POE is OK

## PROTECTION

<b>ESD</b>	Contact discharge: Level III Air discharge: Level III Execute: IEC61000-4-2
<b>Lightening Protection</b>	Level III Execute: IEEE61000-4-5

## OPERATING ENVIRONMENT

<b>Working Temperature</b>	-10°C ~ 55°C
<b>Storage Temperature</b>	-40°C ~855°C
<b>Humidity</b>	0 ~ 96%

## MECHANICS

<b>Dimension (MM)</b>	113 x 45.5 x 29
<b>Material</b>	ABS Plastics
<b>Color</b>	Black
<b>Weight</b>	SV device: 58g IPC device: 58g

## APPLICATION DIAGRAM

