

Features:

- RG6/U 18AWG 75ohm Center Conductor
- Black Color
- 60% braid with bonded foil shield
- Attached 2 Stranded 18AWG 7x0.385mm Black/Red Power Cable
- Ideal for CCTV Surveillance System installation
- ISO 9000 Certified* Spool Reel in box

Specifications:

Color	Black
Length	500 FT
Rating	ETL Listed
Conductor	RG6: CCS (Copper Clad Steel) 18/2: CCAM (Copper Clad Aluminum Magnesium) Stranded
Shielding	RG6: Bonded Aluminum Foil 18/2: PVC
Electrical Properties	Impedance: 78±5Ω Capacitance: 50±2 pF/m Velocity: 85% nom Inner Conductor: <118 Ω/km DC Resistance Outer Conductor: <30 Ω/km DC Resistance SRL: 5-1000MHz≥ 18dB
Attenuation (100m)	Freq. 50 MHz, ≤5.5 dB Freq. 100 MHz, ≤7.86 dB Freq. 200 MHz, ≤10.1 dB Freq. 700 MHz, ≤18.5 dB Freq. 1000 MHz, ≤22.4 dB Freq. 1200 MHz, ≤24.59 dB Freq. 1450 MHz, ≤26.36 dB Freq. 1800 MHz, ≤28.98 dB Freq. 2200 MHz, ≤32.03 dB Freq. 2500 MHz, ≤36.45 dB Freq. 3000 MHz, ≤39.54 dB
Product Dimensions	12 x 11 x 11 inches
Item Weight	35 pounds



Packaging:

