

Features:

- RG59 CCAM(Copper Clad Aluminum & Magnesium) 20AWG Center Conductor+18/2 CCTV Stranded Black/Red Power Cable. One Cable Solution
- 20 AWG CCAM Center Conductor. 95% Coverage Braid Shield
- Attached 2 Stranded CCAM 18 AWG 7x0.385mm Black/Red Power Cable
- White Color PVC jacket
- ISO 9000 Certified * Ideal for composite video, RGBHV video, component video and even surveillance systems

Specifications:

Color	Black
Length	1000 FT
Dielectric	Gas Injected Foam POE
Conductor	CCAM (Copper Clad Aluminum Magnesium)
Shielding	95% Braid Coverage
Jacket	75° PVC U/V BLACK
Nom. Imp (Ω)	75
Nom. Vel of Prop.	82%
Attenuation (100ft)	Freq. 1 MHz, 0,33 dB
	Freq. 10 MHz, 0,88 dB
	Freq. 50 MHz, 1,85 dB
	Freq. 100 MHz, 2,51 dB
	Freq. 200 MHz, 3,58 dB
	Freq. 4000 MHz, 5,29 dB
	Freq. 700 MHz, 7,45 dB
Product Dimensions	13 x 12.9 x 12.7 inches
	Item Weight 34.8 pounds



Structure:

