

Features:

- RG59 combo coax cable with 18 gauge 2 conductor heavily shielded cable is Ideal for Composite Video, RGBHV Video, Component Video and even Surveillance Systems
- Attached 2 Stranded copper 18AWG 7x0.385mm Black/Red Power Cable
- UL Listed 20AWG Center Conductor
- ISO 9000 Certified* 95% Coverage Braid Shield in Spool Box
- The advantages to using RG59 cable is that its more durable and can be run in long distances without interference. You can also cut each security camera run the exact length that you need

Specifications:	
6.1.	AAVI-1
Color	White
Length	500 FT
Dialectric	Gas Injected Foam POE
Conductor	Solid Bare Copper
Shielding	95% Braid Coverage
Jacket	75° PVC U/V WHITE
Nom. Imp (Ω)	75
Nom. Vel of Prop.	82%
Attenuation (100ft)	Freq. 1 MHz, 033 dB Freq. 10 MHz, 0,88 dB Freq. 50 MHz, 1,85 dB Freq. 100 MHz, 2,51 dB Freq. 200 MHz, 3,58 dB Freq. 4000 MHz, 5,29 dB Freq. 700 MHz, 7,45 dB Freq. 900 MHz, 8,7 dB Freq. 1000 MHz, 9,31 dB
Product Dimensions	13.2 x 12.8 x 12.8 inches
Item Weight	37.8 pounds



