

#### Features:

The KPC600AI Pinhole is designed as a discrete, high performance solution. This is one of the smallest cameras available in the market, but it does not lack in performance or image quality. With easy installation, this Micro Camera is an ideal mobile solution and is ideal for helping ATMs determine criminal or fraudulent behavior and provide safer transactions to users as well as valuable visual evidence for security departments when needed.

#### Specifications:

Resolution	2MP 1920(H)×1080(V)
Image Sensor	1/2.8" Progressive CMOS
Min. Illumination	Color 0.1lux @ F1.2(AGC ON)
Shutter	1/5 ~ 1/20000s
Slow shutter	Support
Lens	2.1 mm H.FOV: 141°
F No.	F 2.1 ±5%
Day & Night	Manual
WDR	120 dB
Video Compression	H.265/H.264
Video bit rate	8Kbps ~ 8Mbps
Triple Stream	yes
Frame Rate	<b>Mainstream (1-30fps optional)</b> 1920x1080, 1280x960, 1280x720
	<b>Substream</b> 1280x720, 640x480, 320x240
	<b>Mobilestream</b> 640x480, 320x240
Image Settings:	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
ROI	Support
Privacy Mask	Support
Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection, Cross Counting. DEEP LEARNING: Face Detection, Face Recognition
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF (Profile S)
Interface	RJ45 10M / 100M Ethernet interface x1
Led	NA
IR Range	NA
SD storage	no
Alarm Trigger	no
Audio	yes
Video Output	no
Reset Button	no
PoE	yes
Water Proof	no
Power Supply	DC 12V/POE
Consumption	≤ 4W
Dimension	38X42x25mm
Storage Temperature	-30 ~ +60°C
Operating Temperature	-30 ~ +55°C



#### Appearance size

