

COMPACT-PRO 60 | ref.30900

Thermal spraying machine



Versatile petrol sprayer for exterior spraying. Compact-Pro 60 is a simple and reliable machine made in France.

Different types of application: single-coat fillers, traditional mortars, liquid screed transport, pointing

TECHNICAL CHARACTERISTICS

MOTORISATION

Lombardini	LDW FOCS 1003
Fuel	gasoil
Gasoil reservoir	25 L
Cooling	liquid
Rotation speed	2500 RPM
Cylinders	3
Consumption	3 L/h
Hydraulic circuit	28 L
Compressor	bi-cylinder
Compressor flow-rate at 4 bar	400 L/min

COMMAND PANEL

Motor panel	complete
Hydraulic commands	manual
Mixer rotation speed reg.	yes
Pump speed adjustment	yes
Auto accelerator command	yes

HYDRAULIC RAISING MIXER

Tank capacity	230 L
Drain plug	3"
Water diffusion ramp	yes
Water meter	yes
Pales paddle	yes
Rotation	2 directions
Loading height	86 cm

HOPPER

Tank capacity	200 L
Drain plug	3"
Variable flow-rate	0 to 160 L/min
Pressure	0 to 40 bar
Grain size	6 mm
Pump reverse speed	yes

HP CLEANER

Max. pressure	140 bar
Flow-rate	11 L/min

DIMENSIONS

Overall length with arrow	3,55 m
Overall length without arrow	3,09 m
Overall width	1,26 m
Higher point height	1,29 m
Weight with full fuel	720 kg
Noise level	101 Lwa
Outlet height	40m
Max. hose length	100 lm

DELIVERED WITH:

- 1 MAP 10 pump
- 1 Ø35 x 13,30 m product hose 50M x 35F
- 1 Ø35 x 13,30 m product hose 35M x 35F
- 1 Ø25 x 5m hose 35M x 25M
- 1 Ø10 x 33m air hose
- 1 spraying lance
- 8 nozzles (Ø8, 10, 12, 14, 16, 18, 20 & 22)
- 3 pointing nozzles (Ø10, 12 & 14)
- 2 Ø30 foam cleaning balls
- 2 Ø50 foam cleaning balls
- 1 greasing pump with a grease cartridge
- 1 pressure controller adapter
- 1 pressure controller
- 1 complete high pressure washer lance
- 1 10m high pressure washer hose
- 1 storage carry-case
- 1 suspension strap