




# LPT44

## Lithium Pallet Truck

Patents pending



**CAPACITY 2000 kg**

### EASY EXCHANGE LITHIUM ION BATTERY

48-volt 30AH rechargeable  
240v 13.5A plug-in internal charger

### DRIVE AND TRAVEL CONTROLS

48-volt Curtis travel control with permanent magnet drive motor.

Variable speed from 0 to 6 km/h empty  
Variable speed from 0 to 5.3 km/h loaded

### WEIGHT

249kg with battery

### TIRES

Drive (1) 245 x 94 polyurethane  
Load (2) 2x 80x85/ 80x115 polyurethane

### FORKS 685mm OAW x 1170mm OAL

Designed for use with standard 1220mm pallets and other common skids and containers. Forks can achieve a maximum elevation of over 216mm and are built for heavy duty use and come standard with a robust fork entry roller for reliable pallet entry.

### CONTROL HEAD

Travel, lift, and lower functions are located on the ergonomic control head. All operator controls are accessible without having to lift one's hand from the handle grips. The control head is designed to allow for easy operation of with either hand and includes a belly button reversing switch, dual butterfly travel controls, horn, and battery discharge indicator and key switch. The low mounted tiller arm offers excellent operator comfort and minimum steering effort.

### HYDRAULICS

DC pump and chrome plated cylinder provide for smooth and efficient lifting.

### ELECTRICAL

Water resistant connectors and shrouded wiring harness supply power reliably to components. System includes an emergency power disconnect and covered on-board dock for the Easy Exchange HD Battery.

### BRAKES

Electromechanical brake provides good stopping power when handle is upright or lowered beyond the operating range.

### SERVICEABILITY

Removable covers and modular design of components provides for easy maintenance with simple hand tools. Two piece drive wheel reduces complexity of tire changes.

### DUTY CYCLE

Revolutionary Easy Exchange HD Battery delivers up to 3.5 hours of operation and can be fully charged within 2 hours. Optional extra batteries can be purchased to extend run time or to serve as a reliable back-up.



### OPTIONAL

- 1220mm load back rest
- Traction tire
- Stability casters
- Extra Easy Exchange HD batteries and an optional external charger are available to support a virtually infinite duty cycle.

