



Drophog Nylon Weight Belt **Instructions** (Right Handed Setup)

Step 1: Take the black belt in your left hand, and the buckle in your right hand as shown below. Logo upside down.



Step 2: With the buckle open, insert the nylon belt through SLOT 1 from the top down.



Step 3: Thread the nylon belt through SLOT 2 from the bottom up. Pull the belt all the way through taking away any slack.



Step 4: Thread the nylon belt through SLOT 3 from the top to the bottom as shown. Pull all the way through and remove slack (as shown in Inset A). Inset B shows the weave direction as performed in steps 1 through 3 for reference.



Step 5: Flip the buckle over and pull tight the nylon belt and expose the hole in SLOT 1 that remains (SLOT 1 is larger than SLOT 2 and 3 to accommodate two layers of belt) proceed to thread the belt back through SLOT 1 from the bottom. This way the "tail" will rest underneath the belt when it is worn.



Step 6: Once you feed the "tail" all the way back through SLOT 1 the belt will be threaded through the buckle and be ready to be worn.



Step 7: At this point your belt and buckle should be assembled to be worn in a "right handed" quick release set-up. Fit around your waist to the desired tightness and secure the quick release buckle by pressing it firmly closed. The teeth on the inside of the buckle will "grab" the nylon belt in the secured position. Simply lift up on the tab to release the buckle.

You can now add your desired weights and should be ready for diving.

