



# 100TM

TETHER MOUNT (For Family Vehicle)

## IMPORTANT INFO

- Meets FMVSS213.
- Use Only with EZ-ON Vests. Compatible Vest include: 303Z, 403PB.
- Install tether hardware kit if the passenger weight exceeds the vehicles tether anchor weight determined by the vehicle manufacturer.
- Must use factory seatbelt.

## WARRANTY

*EZ-ON Products stands behind the products we make. Warranty covers any defects in material or workmanships under normal use during the warranty period. We will repair or replace product defects for 1 year from manufacturer date.*

## WARNING

Death or serious injury can occur if manufacturer's instructions are not followed correctly. All EZ-ON products are dynamically tested to meet NHTSA standards. Please follow washing instructions on product tag. Replace product if it is damaged, frayed, or has been in a crash. Recommended replacement after six years. EZ-ON Products are not liable for injury if these recommendations are not followed.

## EMERGENCY RELEASE PROCEDURE

### EMERGENCY CUTTING

When evacuating the passenger in a safety vest, the vest webbing is never cut. One cut of the mount webbing above the anchor will allow the passenger to evacuate the vehicle wearing the safety vest and one cut of the lap belt.

**CUT ALONG DOTTED LINE FOR EMERGENCY RELEASE**



**100 SCBC  
EZ-ON Safe Cut  
Belt Cutter**








# 100™

## TETHER MOUNT

(For Family Vehicle)

### INSTALLATION INSTRUCTIONS



1. Locate tether anchor bracket.

\* Check vehicle owner's manual to locate factory installed tether bracket.

\* Instructions for hardware kit are found in the Tether Kit assembly bag.

2. Attach snap hook of tether mount to car's tether anchor.

3. Place the "Y" of tether mount over back of the seat.

4. Tighten strap by pulling webbing through tilt lock adjuster.

5. With passenger properly seated (hips low against back of seat and shoulders flush to seat). Attach each snap hook at end of the "Y" to tether slots in shoulder adjusters.

6. Reduce tether slack by lifting tilt lock adjuster upward. Slide the webbing to loosen or tighten.

\* Passenger's shoulders must be held tight against back of seat.

7. Thread vehicle belt through vest loops.

8. Buckle belt low on the lap.

9. Secure seatbelt as tightly as possible. Make sure the seat belt is in a locked position.