



**EZ-ON
PRODUCTS**

MAXPV VEST

INSTALLATION INSTRUCTIONS

IMPORTANT INFO

- Meets FMVSS213 when used with MAXPV Mount
- For use by passengers weighing 31 - 168LBS
- Must be used with MAXPV Mount (100MPV)
- Follow washing instructions on product tag
- EZ-ON Products must be worn under winter jackets
- Sizing (according to chest measurements)
- XS 18" - 24" | S 25" - 32" | M 32" - 37" | L 37" - 43"
- Custom Sizing Available



WARNING

Death or serious injury can occur if manufacturer's instructions are not followed correctly. Read below warning information for replacement recommendations.



REGISTER

Register this transportation vest to be notified of a safety recall.




WARRANTY

EZ-ON Products stands behind the products we make. Warranty covers any defects in material or workmanships under normal use during the warranty period. We will repair or replace product defects for 1 year from manufacturer date.

WARNING: All EZ-ON products are dynamically tested to meet NHTSA standards. Replace product if it is damaged, frayed, or has been in a crash. Recommended replacement period is six years. EZ-ON Products are not liable for injury if these recommendations are not followed.

PINCH TEST PROCEDURE

Tighten vest so that no pinch in the webbing can be achieved on the chest strap. When vest is snug fingers will be unable to grab any webbing.



605 Commerce Way West
PO Box 660
Jupiter, FL 33458

561.747.6920
cs@ezonpro.com

EZONPRO.COM



**EZ-ON
PRODUCTS**

MAXPV VEST

SCAN CODE TO VIEW VIDEO
INSTRUCTIONS & MORE



INSTALLATION INSTRUCTIONS



1. Hold vest while passenger steps into crotch straps with the EZ-ON® parachute logo in front.



2. Choose one of the (3) zippers that fits child snugly. Be certain that the vest fits secure.



3. Hook zipper lock into zipper pull. Keep bottom strap low around the hip level.



4. Adjust crotch straps to shorten or lengthen, to be snug but not tight. Keep the bottom strap low around the hip level.



5. Adjust shoulder straps using adjusters. Pull webbing through adjuster to reduce slack. Do not pull too tight as this will cause vest to pull up off hips resulting in injury.



6. Back thread web through bar slides to lock.