

Repairs to Coolabah G2 Awning Replacing the Tiller Joint on the Container



Use a screwdriver to pop out the screw covers and then unscrew the end cap.

Take note of which way the arms move, consider taking a photo before proceeding to the next step.





Slide out the metal return holder and the arm.

Do not remove the plate with the bolt in it.

A small amount of silicone spray will assist if the fit is tight.





Use a hammer and punch to push the pin out far enough that it can be pulled out with pliers.





www.aussietraveller.com.au

When the pin has been removed, pull out the tiller joint – pliers may be required if the tiller joint is broken.

If there is not enough shaft to grab with pliers, push it through into the tube with a small screwdriver.

The bush may come out with the tiller joint, retain the bush for reuse.

11-15 Oasis Court, Clontarf, QLD 4019 Phone: 07 3284 3284 Fax: 07 3284 5969 E-mail: enquiries@aussietraveller.com.au

E-mail: info@aussietraveller.com.au



AUSSIE TRAVELLER

Incorporated in Queensland A.C.N. 010 809 168 A.B.N. 81 010 809 168





Push the bush and tiller joint into place. A gentle tap with a hammer may be required.

When it's firmly in place, drill through the tiller joint with a 5mm drill bit via the hole in the tube where the pin used to be.



Fit the new pin into the hole and tap into place. It must be visible on both sides of the tube in order to lock the tiller joint into place.





Slide the arm and metal return holder back into place, ensuring that everything is facing the correct direction (refer to the first step) and screw the end cap back on.

Tap the screw covers back into place.

www.aussietraveller.com.au

E-mail: info@aussietraveller.com.au