



Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043

Phone (03)9350 4188

Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

ACRYLIC TRIM SATIN AND GLOSS

Description

A high performance acrylic water thinned paint that dries to a durable finish for painting interior and exterior trim. It has been developed to replace the use of the high VOC solvent enamels.

It has low odour and dries very quickly to a gloss finish. It has excellent block resistance and dries to a hard enamel like finish that forms a very tough film that can be easily cleaned. Some properties such as gloss level, flow and leveling are slightly compromised when compared to solvent enamels but the improvement in the environmental, health and safety issues more than compensate for this.

Use

On all interior and exterior trim including doors, skirting boards, windows and architraves.

Surface Preparation

Ensure the surface is dry and clean of dirt, grease and dust.

New surfaces – Fill holes and joints then sand and dust off. On exterior surfaces apply appropriate primer, on interior surfaces no primer is necessary – apply Vipond's Easy Sand Undercoat and sand with 240-320 free cut sandpaper.

Previously painted – Scrape off all loose and flaking paint and sand glossy surfaces. Surface should be free from dust, grease and powdery material. Wash down with sugar soap. On sound even surfaces there is no need to use an undercoat. On patchy or bare surfaces apply appropriate primer on exterior surfaces and for interior surfaces apply one coat of Vipond's Easy Sand undercoat and lightly sand.

Application

Thoroughly stir the paint. It is best applied with a brush on narrow trim areas but on large flat areas such as doors apply with a roller (6mm nap). Cut in with a brush and allow to partly dry (at least 10 minutes) then roll the entire area. Do not apply heavy coats or sagging may occur. For best results apply two coats. Apply only if the temperature is above 10°C. Where the product is drying to quick for application purposes Viponds Hot Weather thinner is recommended

It has excellent spraying characteristics through Air Assisted Airless Sprayers and HVLP guns. Apply two medium coats allowing the first coat at least one hour to dry.

Drying

Under normal drying conditions (low humidity and temperature between 16°C and 25°C) it will touch dry in 15 minutes and can be recoated after 2 hours. If the product is drying too quickly add Vipond's hot weather retarder.

Clean up and Thinning

Use clean water only.

Coverage

14 - 16 square metres per litre per coat.

Colours

White , factory milled black and mid tone colors. Where bright accent colors are required and tough durable finish is needed Viponds Ecoshield is recommended

Pack Size

500 mls,1 litre and 4 litre

Revised January 2021