



## Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043

Phone (03)9350 4188

Email [info@viponds.com.au](mailto:info@viponds.com.au)

[www.viponds.com.au](http://www.viponds.com.au)

### PRODUCT INFORMATION

## ACRYLIC EASY SAND UNDERCOAT

### Description

A premium quality water based undercoat for interior use that has high opacity, excellent filling properties and is very easy to sand.

### Use

It will seal and undercoat customwood, craftwood, MDF, plywood and solid timbers ready for oil or water based topcoats. It's "easy sand" property makes it the ideal undercoat for gloss enamel finishes. It is also suitable as an undercoat / sealer for plasterboard, cement, brick or masonry.

### Surface Preparation

Sand then fill all holes with appropriate filler and dust off. Sand previously painted areas and ensure the surface is dry and clean of dirt, grease and dust.

**Customwood, MDF, Timber** - Apply easy sand undercoat and allow to dry. Sand before applying top coat. On surfaces that require a mirror finish apply a second coat and sand with 240-320 freecut sand paper.

**Plasterboard, Cement, Masonry** - Thin the paint with approximately 5 to 10% water. This will aid roller application to allow the paint to spread evenly on broad wall surfaces.

### Application

Thoroughly stir and apply with brush, roller or spray.

### Drying

Under normal drying conditions (above 15°C and low humidity) it will be touch dry within 30 minutes and can be sanded after 2 hours. Recoat after 2 hours. Do not apply if temperature is below 10°C.

### Clean up and thinning

Use clean water only

### Coverage

12 - 14 square metres per litre per coat

### Pack Size

500ml, 1 litre, 4 litre, 10 litre

Revised January 2021