



## Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043

Phone (03)9350 4188

Email [info@viponds.com.au](mailto:info@viponds.com.au)

[www.viponds.com.au](http://www.viponds.com.au)

## PRODUCT INFORMATION

### ACRYLIC FLAT

#### Description

A water thinned acrylic paint that has high opacity and dries to a flat finish. Suitable for interior surfaces and is available in white, pastel shades and deep accent tones.

#### Use

On interior broad wall surfaces when a flat finish is required. A flat finish reduces light reflectance and therefore helps to hide surface imperfections. Used in the home for ceilings and walls and for feature work on displays and signs. Flat finishes soil very easily from dirty hands and finger marks and are difficult to clean. Excessive rubbing to clean an area can increase the sheen level and make the surface look patchy. If a more washable finish is required then Vipond's Low Sheen Acrylic is recommended.

#### Application

Apply with brush, roller or spray. One coat coverage is possible where primed / previously painted with correct background color but for a perfect finish apply two even coats.

#### Surface Preparation

Ensure the surface is dry and clean of dirt, grease and dust.

*Plasterboard* – Fill holes and joins, dust off and apply Viponds Acrylic Sealer Undercoat followed by one or two coats of acrylic flat.

*Brick and Masonry* – Remove all loose and powdery material with a stiff brush and wash down with water. Apply a coat of Vipond's Multipurpose Primer Undercoat Sealer.

*Previously Painted Surfaces* – Scrape off all loose and flaking paint and sand glossy surfaces. Should be free from dust, grease and powdery material. Wash down with sugar soap. Undercoat bare areas with Viponds Acrylic Sealer Undercoat. When using deep tone colours apply a white or light grey undercoat to provide a surface which is even in colour and texture. This will ensure true colour and help coverage.

#### Drying

Under normal drying conditions (low humidity and temperature between 16°C and 25°C) it will be touch dry in 30 minutes and can be recoated after 2 hours.

#### Clean Up and thinning

Use water

#### Coverage

14 - 16 square metres per litre.

#### Pack Size

1 litre, 4 litres, 10 Litre and 15 Litres

#### Colours

Colour card and customer specifications.