



Vipond's Paints Pty Ltd
58 Barrie Road, Tullamarine VIC 3043
Phone (03)9350 4188
Email info@viponds.com.au
www.viponds.com.au

PRODUCT INFORMATION

ACRYLIC LINE MARKING

Description

A fast drying water based paint for marking lines on asphalt and concrete surfaces. It may also be applied directly onto brick, masonry and galvanized metal

Use

It is a new generation acrylic that has excellent durability and is suitable for roads, carparks, kerbing and pavements. Although it is fast drying it is suitable for brushing and rolling. Glass beads can be scattered onto the applied paint to improve light reflection

Application

Brush, roll or spray.

Surface Preparation

Ensure the surface is clean and free of oil and grease and only apply to dry surfaces. Clean with a high pressure water cleaner.

Allow new asphalt to weather and cure for at least one month before applying line marking paint.

Allow new concrete to cure for at least one month.

Drying

Under normal drying conditions (above 15 °C and low humidity) it will be touch dry within 15 minutes and can be recoated within 2 hours. Drying times will vary depending on film thickness, ventilation and weather conditions.

Clean Up and Thinning

Thin and clean up with water.

Coverage

8 - 10 square metres per litre.

Pack Size

1 , 4 litre and 10 litres

Colours

Black, white, safety yellow, red and blue and customer specifications.

Revised January 2021