



Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043

Phone (03)9350 4188

Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

ACRYLIC METAL PRIMER

Description

A water thinned acrylic paint containing rust inhibiting zinc phosphate with excellent adhesion properties to metal.

Use

It is primarily used as a primer on treated metals such as galvanized steel and zinc alume but it is also used on steel as it contains zinc phosphate to inhibit rust. Overcoat with water or oil thinned topcoats.

Application

Thoroughly stir and apply with brush, roller or spray. Apply a thin even coating.

Surface Preparation

The metal must be completely free of dirt, grease, oil and rust. Treat any rust with a rust converter. Galvanised surfaces should be washed with mineral turpentine or solvent degreaser. Follow by wiping over with methylated spirits or IPA.

Drying

Under normal drying conditions (15°C and low humidity) it will be touch dry within 30 minutes and can be recoated after 2 hours. Do not apply if the air or substrate temperature is below 10° C. Where the product is drying to quick for application purposes Viponds Hot Weather thinner is recommended

Coverage

Approximately 14 square metres per litre.

Cleaning and Thinning

Use clean water only.

Pack Size

500ml, 1L, 4L, 10L

Colour

White and grey. Other colours made to order

Revised January 2021