



## Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043

Phone (03)9350 4188

Email [info@viponds.com.au](mailto:info@viponds.com.au)

[www.viponds.com.au](http://www.viponds.com.au)

## PRODUCT INFORMATION

### ARTISTS ACRYLIC PAINT

#### Description

A versatile premium quality acrylic paint for art, craftwork, folkart and murals. Available in gloss and matt finish for interior and exterior use.

Use **gloss** if you want your art work to stand out and to be striking and vibrant.

Use **matt** if you want a more traditional, subtle finish. Easier to work with and can be overcoated with Viponds Graffiti Coat (Gloss) if required.

Gloss and Matt can be mixed together to achieve varying gloss levels.

#### Use

This product is very versatile and can be used for all forms of painting. The artist can achieve impasto, gouache and water colour effects from the one paint. Add Viponds Acrylic Thickener or Impasto gel to thicken and just add water to thin. Use it to decorate craft items made from terracotta, plaster, fabric, paper metal and timber. Due to the exterior durability of the pigments it is ideal for long term outdoor mural work.

#### Surface Preparation

It is important to prepare the surface properly to achieve long term adhesion. Ensure the surface is sound, dry and clean of dirt, grease and dust. It is always best to apply over a white undercoat to achieve vibrancy of colour.

For exterior murals it is particularly important to prepare the surface for long term durability.

**Timber** – Sand, dust down and apply a coat of wood primer. Fill holes with filler.

**Galvanised Iron and Aluminium** – Remove oil and grease. Apply Acrylic metal primer or an etch primer

**Iron and steel** – Remove oil, grease and rust. Treat any remaining rust with a rust converter then apply Viponds Acrylic metal primer or etch primer.

**Brick and Masonry** – Remove all loose and powdery material with a stiff brush and wash down. Apply a coat of Viponds Multi-purpose Primer Sealer Undercoat. – white.

**Previously painted** – Scrape off all loose and flaking paint and sand glossy surfaces. Wash down with sugar soap. Check adhesion of remaining paint. Spot prime bare wood and metal with appropriate primer. Apply a coat of Viponds Multipurpose undercoat - white over the total surface.

**Application**

Brush, roll or spray. Apply at least two coats for durability and for a perfect finish.

**Drying**

Under normal drying conditions (above 15°C and low humidity) it will touch dry in 30 minutes and can be recoated after 2 hours. Do not apply if the temperature is below 10°C.

**Clean up and Thinning**

Use clean water only.

**Coverage**

14 - 16 square metres per litre per coat.

**Pack Size**

200 mls 1 litre 4 litre

**Colours**

Colour card and customer specifications.

Revised January 2021