



Vipond's Paints Pty Ltd
58 Barrie Road, Tullamarine VIC 3043
Phone (03)9350 4188
Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

CEILING PAINT

Description

A premium water thinned acrylic paint that has high opacity and dries to a flat finish. It is easy to apply and is spatter resistant.

Use

This product is ideal for ceilings. It has a flat finish which reduces light reflectance and this will help hide any surface imperfections. The paint has high viscosity, allowing a high film build which provides one coat coverage in most cases

Application

Apply with brush, roller or spray. One coat coverage is possible but for a perfect finish apply two even coats.

Surface Preparation

Ensure the surface is dry and clean of dirt, grease and dust.

Plasterboard – Fill holes and joins, dust off and apply Viponds Multipurpose primer Sealer, Undercoat followed by one or two coats of acrylic flat.

Previously Painted Surfaces – Scrape off all loose and flaking paint and sand glossy surfaces. Should be free from dust, grease and powdery material. Wash down with sugar soap. Undercoat bare areas with Viponds Multipurpose primer Sealer, Undercoat. An adhesion test is recommended to ensure that the existing painted surfaces is in sound condition.

Drying

Under normal drying conditions (low humidity and temperature between 16°C and 25°C) it will be touch dry in 30 minutes and can be recoated after 2 hours.

Clean Up and thinning

Use water

Coverage

14 - 16 square metres per litre.

Pack Size

10 litres, 4 litres , 1 litre and 500mls

Colours

Colour card and customer specifications.

Revised January 2021