



Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043

Phone (03)9350 4188

Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

CONCRETE and MASONRY SEALER

Description

A water thinned acrylic clear for sealing concrete and masonry. It penetrates the surface to form a thin coating that will prevent efflorescence coming to the surface.

Use

It is used to protect finishing coats such as Ecopave or Viponds Acrylic Low Sheen on masonry from being attacked by the alkaline salts (efflorescence) in new concrete and masonry. It has exterior durability and may be used as a clear coat to seal and protect concrete and masonry surfaces that are to maintain their natural colour.

Application

The sealer is ready for use and can be applied with a brush, roller or spray. One coat is sufficient when it is used as a sealer but at least two coats are required when being used as a clear coat.

Surface Preparation

The cement or masonry should be allowed to cure for at least one month but preferably 3 months. Thoroughly clean the surface then acid etch – prepare a solution of 1 part spirits of salts (33% hydrochloric acid) and 3 parts water. Apply liberally and scrub the surface with a stiff broom.

Allow at least 10 minutes for the solution to react before thoroughly washing with water to remove all traces of reacted salts. On smooth steel trowelled concrete repeat the procedure.

Drying

Under normal drying conditions (above 15°C and low humidity) it will touch dry in 30 minutes and can be recoated after 2 hours. Allow at least 6 hours before applying other top coats.

Clean up and Thinning

Use clean water only.

Coverage

8 - 10square metres per litre per coat.

Pack Size

1 litre, 4litre and 10 litres

Revised January 2021