



Vipond's Paints Pty Ltd

2 Norris Street North Coburg 3058
Phone (03) 93504188 Fax (03) 93542732
Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

ECO-CLEAR

Description

Vipond's ECO-Clear is a urethane waterbased clear coat that provides similar properties of conventional solvent based polyurethanes. It dries to a hard durable finish with excellent abrasion and scuff resistance and has good resistance to heat and household chemicals. It is low odour, non-yellowing, and dries quickly to allow faster recoat times. Waterbased allows easy clean up. Ideal for all interior timber surfaces such as tables, doors, cupboards, furniture, trim and wall panelling. It has excellent adhesion to enamel finishes and is an ideal finishing coat over Vipond's Scumble Medium.

Surface Preparation

Uncoated Timber - Ensure the surface is free of dirt, grease and powdery material. Fill all holes with wood filler and allow to dry. Sand smooth and remove dust. For best results, always sand in the direction of the grain.

Previously Coated Timber - Ensure the surface is free of dirt, dust, grease and loose or powdery material. If the previous coating was a single pack polyurethane, then lightly sand glossy surfaces and remove dust. If the previous coating was unknown, then remove it entirely by sanding and remove dust.

Application

Thoroughly stir EcoClear with a broad flat stirrer. Stir gently to minimise aeration. Apply with a brush, pad applicator or spray. To optimize application, it can be thinned sparingly with water. Apply a minimum of two coats. Often the first coat will raise the timber grain. For best results, lightly sand the first coat with fine grit sandpaper, then apply subsequent coats.

If the timber is stained, a wash with an oxalic acid solution and rinse with water prior to application may assist with stain removal. Sanding the affected area may also assist with stain removal.

Drying

Under normal drying conditions (low humidity and temperature between 16°C and 25°C) it will touch dry in 30 minutes and can be recoated after 2 hours.

Clean up and Thinning

Use clean water only.

Coverage

10 - 12 square metres per litre per coat.

Pack Size

1, 4 and 10 litres.

Finish

Gloss, Satin and Matt.