

Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043 Phone (03)9350 4188 Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

ECOPAVE CLEAR

Description

Vipond's Ecopave is a new generation water based paving paint that has exceptional durability and is suitable for direct application onto prepared concrete and primed timber.

Unlike traditional oil based paints it is efflorescence and alkali resistant, and therefore is a superior product on concrete. It has excellent hot tyre resistance.

Easy to apply, dries to a satin finish and has good slip resistance for interior and exterior surfaces. It dries quickly and can be recoated in 2 hours.

Ecopave Clear is used to overcoat Ecopave colours to achieve a gloss finish which in turn will minimize marking and make it easier to clean. The negative effect is the floor will be much more slippery when wet. Ecopave clear gloss is also suitable to protect other painted surfaces such as Viponds Artist Matt and Artist Gloss

Surface Preparation

When applying to freshly painted Ecopave ensure that the Ecopave is completely dry. Allow at least 24 hours before overcoating.

Over aged Ecopave thoroughly clean with detergent and scrubbing brush then rinse thoroughly. Allow the surface to dry.

Application

Thoroughly stir with a broad flat stirrer. Do not shake. Apply with a brush, pad applicator or spray. Do not use a roller because it may produce bubbles. For a high gloss apply a second coat.

Drying

Under normal drying conditions (above 15°C and low humidity) it will be touch dry within 30 minutes and can be recoated after 2 hours. Do not apply if the temperature is below 10°C. or above 30°C. Damp and humid conditions will change the drying times.

Under normal drying conditions it may be walked on after 2 hours but it is best to leave for 24 hours.

Clean up and thinning

Use clean water only.

Coverage

12 to 14 square metres per litre per coat ..

Pack Size

2 litre, 4 litre and 10 litre