



## Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043

Phone (03)9350 4188

Email [info@viponds.com.au](mailto:info@viponds.com.au)

[www.viponds.com.au](http://www.viponds.com.au)

### PRODUCT INFORMATION

## HIGHCOVER UNDERCOAT

### Description

A premium oil based all purpose undercoat. It has good exterior durability with excellent filling and sanding properties. Along with high opacity it provides excellent gloss holdout for enamel topcoats.

### Use

This product has excellent adhesion, opacity and good sanding properties. It can be used on properly primed exterior surfaces and on previously painted surfaces. It is ideal as a one coat primer/undercoat on interior woodwork.

Not suitable as a primer coat on MDF.

### Application

Brush, roller or spray.

### Surface Preparation

Ensure the surface is dry and clean of dirt, grease and dust.

*Timber* – All exterior timber should be sanded and primed with Vipond's Oil Pink Primer. Allow at least 24 hours to dry then apply Highcover Undercoat. On interior surfaces sand timber then apply Highcover Undercoat.

*Metal* - Use Vipond's Zinc Phosphate Metal Primer or Acrylic Metal Primer on galvanised iron. Then apply Highcover Undercoat.

*Brick, Concrete, Masonry* - Apply Vipond's Acrylic Clear Sealer followed by one coat of Highcover Undercoat.

*Previously Painted* - Thoroughly clean removing all dust, grease and loose and flaking paint. Sand glossy surfaces, prime bare areas then apply Highcover Undercoat.

### Drying

Under normal drying conditions (above 15°C and low humidity) it is touch dry within 4 hours and can be recoated after 16 hours. Do not apply if the temperature is below 10 °C.

### Coverage

Approximately 14 square metres per litre.

### Clean Up

Use mineral turpentine for cleaning and thinning.

### Pack Size

500 ml, 1 litre, 4 litre, 10 litre

### Colour

White and grey.

Revised January 2021