

# **Vipond's Paints Pty Ltd**

58 Barrie Road, Tullamarine VIC 3043 Phone (03)9350 4188 Email info@viponds.com.au

www.viponds.com.au

#### PRODUCT INFORMATION

#### INTERIOR ACRYLIC LOW SHEEN

# Description

A premium quality acrylic water thinned paint that has excellent durability on interior surfaces. It is easy to apply with no roller spatter and has high opacity with low odour and mould resistance.

#### Use

Suitable for interior areas such as bedrooms, hallways and lounge rooms when a low sheen (approx. 7% gloss) and washable finish is required. Use on all interior broad wall surfaces such as plasterboard, brick and masonry.

### **Application**

Thoroughly stir and apply with brush, roller or spray. Requires two coats for a perfect finish.

### **Surface Preparation**

Ensure the surface is dry and clean of dirt, grease and dust.

**Plasterboard** – Fill holes and joins, dust off and apply one coat of Vipond's Multi Purpose Primer Undercoat Sealer followed by one or two coats of Interior Low Sheen Acrylic. **Brick and Masonry** – Remove all loose and powdery material with a stiff brush and wash

down. Apply one coat of Viponds Acrylic Sealer Undercoat

**Previously painted** – Scrape off all loose and flaking paint and sand glossy surfaces. Wash down with sugar soap. When using deep tone colours apply a white or light grey undercoat first. This will ensure true colour and help coverage. An adhesion test may be required on the existing paint.

### **Drying**

Under normal drying conditions (above 15° C and low humidity) it will touch dry in 30 minutes and can be recoated after 2 hours. Do not apply if the temperature is below 10°C.

# Clean up and thinning

Use clean water only.

#### Coverage

14 - 16 square metres per litre per coat

#### Pack Size

500 ml, 1 litre 2 litre, 4 litre and 10 litre

#### **Colours**

Colour card and customer specifications. White, factory milled black and tinted to unlimited colour range including Pantone colours.