



Vipond's Paints Pty Ltd
58 Barrie Road Tullamarine VIC 3043
Phone (03) 9350 4188
Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

PINK PRIMER

Description

A linseed oil based primer formulated to penetrate into raw timber surfaces. It regulates any moisture entering and leaving the timber to minimize cracking of the timber. It provides an excellent basecoat for finishing with oil or acrylic top coats.

Use

Suitable for all interior and exterior timber. Its primary use is a primer not a filler. Use an undercoat to fill the grain in the timber. It will prevent tannin stains bleeding into top coats. Do not apply on painted surfaces.

Application

Best application is by brush or roller, working the primer into cracks, joints, nail holes and end grain.

Surface Preparation

Remove all dust, dirt and grease and sand timber to a smooth surface. Ensure the surface is dry. On previously painted timber remove all loose or flaking paint and sand timber. Ensure the timber is dry and only apply primer to bare timber (ie spot prime). Fill holes and cracks with linseed oil putty after application of primer. If finishing with acrylic reprime over putty.

Drying

Under normal drying conditions (above 15°C and low humidity) it is surface dry within 8 hours and can be recoated after 24 hours. If using acrylic topcoats allow at least 48 hours before overcoating.

Coverage

Approximately 10 - 12 square metres per litre.

Clean Up

Use mineral turpentine for cleaning and thinning.

Pack Size

500 ml, 1 litre, 4 litre,

Colour

Pink

Revised August 2021