



Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043

Phone (03)9350 4188

Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

EXTERIOR ACRYLIC LOW SHEEN

Description

A 100% acrylic water thinned paint that dries to a matt finish and is available in white, pastel and deep accent tones. Superior exterior durability—decorates and protects the surface from extreme weather conditions.

Use

This product has excellent opacity using the most light fast pigments for exterior use. Suitable on a variety of substrates such as brick, cement render, masonry, plasterboard, metal and timber. Use on all exterior surfaces in the home and on display and feature sign work when a matt finish is required. It may also be used on all interior surfaces. This product is ideal for exterior murals due to the light fast pigments and extensive colour range.

Application

Thoroughly stir and apply with brush, roller or spray. Requires two coats for a perfect finish.

Surface Preparation

Ensure the surface is dry and clean of dirt, grease and dust.

Timber – No primer is necessary unless the timber is tannin rich in which case apply tannin resistant Wood Primer. Sand and dust down all bare timber and fill holes prior to painting.

Galvanised Iron and Aluminium – Remove oil and grease with Prep wash. Apply acrylic metal primer or etch primer.

Iron and steel – Remove oil, grease and rust. Treat remaining rust with a rust converter then apply Acrylic Metal Primer or an Etch Primer.

Brick and Masonry – Remove all loose and powdery material with a stiff brush and wash down. No primer required. Undercoat depending on top coat colour.

Previously painted – Scrape off all loose and flaking paint and sand glossy surfaces. Wash down with sugar soap. Spot prime metal with appropriate primer. An adhesion test of the existing coating is recommended prior to painting.

When using deep tone colours such as Lemon Yellow and VIP Red apply a white or light grey undercoat first. This will ensure true colour and enhance coverage.

Drying

Under normal drying conditions (above 15° C and low humidity) it will touch dry in 30 minutes and can be recoated after 2 hours. Do not apply if the temperature is below 10°C. In hot weather conditions use Viponds Hot weather thinner to help application.

Clean up and thinning

Use clean water only.

Coverage

12 - 16 square metres per litre per coat.

Pack Size

500 ml, 1 litre, 4 litres and 10 litres.

Colours

Colour card, customer specifications, RAL Colours , Australian Standard Colors and pantone colours.

Revised January 2021