



## Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043

Phone (03)9350 4188

Email [info@viponds.com.au](mailto:info@viponds.com.au)

[www.viponds.com.au](http://www.viponds.com.au)

## PRODUCT INFORMATION

### QUICK DRY ENAMEL

#### Description

A ready to use quick drying urethane enamel formulated to give high opacity and a full gloss finish. It dries to a very hard tough finish with high abrasion and chemical resistance and excellent durability.

#### Use

Use on all interior and exterior surfaces instead of a gloss enamel when a faster dry time is required or when a harder, tougher and chemical resistant finish is required. Use it on buildings for facias, frames, doors and shelving. It is particularly suitable for metal surfaces such as machine and plant equipment, trailers, handrails, gates and furniture. Ideal as a paving paint on concrete, timber and metal floors.

#### Surface Preparation

To ensure maximum durability and gloss level, surface preparation is most important.

**Timber** – Sand timber and dust off and apply Vipond's Oil Pink Primer followed by Quick Dry Undercoat then one or two coats of Quick Dry Enamel. Primer is not necessary for interior timber, use Viponds Acrylic Easy Sand Undercoat instead.

**Metal** - Prepare metal and apply appropriate Metal Primer then one or two coats of Quick Dry Enamel.

**Brick, Cement, Masonary, Plaster** - Prepare then apply Vipond's Multipurpose Acrylic Undercoat or concrete and masonry sealer.

**Concrete** – Allow new concrete to cure for at least 3 months and ensure old concrete is clean of oil and grease. Acid etch. Refer to Vipond's Fact Sheet – "PAINTING CONCRETE" to determine the suitability and preparation for painting.

**Previously Painted Surfaces** should be free from dust, grease and loose or powdery material. Wash down with sugar soap, spot prime and then apply Quick Dry Undercoat followed by one or two coats of Quick Dry Enamel.

#### Application

Thoroughly stir the paint and apply with brush, roller or spray..

#### Drying

Under normal drying conditions (15°C and low humidity) it will be touch dry within 2 hours. Through dry in 12 hours. Recoat after 16 hours. Do not apply if temperature is below 10° C or in high humidity.

#### Cleaning and Thinning

Mineral Turpentine for brushing or rolling and Vipond's Fast Dry Thinners for spraying.

**Coverage**            Approximately 14 square metres per litre per coat..

**Pack Size**            10 litre, 4 litre, 1 litre.

**Colours**              Colour card and customer specifications.

Revised January 2021