



Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043

Phone (03)9350 4188

Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

ROADMARKING PAINT

Description

A fast drying oil based paint for marking lines on asphalt and concrete surfaces.

Use

Ideal for all interior and exterior surfaces. Although it is fast drying it is suitable for brushing and rolling. Glass beads can be scattered onto the applied paint to improve light reflection.

Although this product has good durability it is recommended to use Viponds Waterbased Linemarking for improved exterior durability and for new concrete surfaces.

Application

Brush, roll or spray.

Surface Preparation

Ensure the surface is clean and free of oil and grease and only apply to dry surfaces.

Allow new asphalt to weather and cure for at least one month before applying roadmarking paint.

New concrete must cure for at least one month and be free from efflorescence. Acid etching will give the best results.

Drying

Under normal drying conditions (above 15 °C and low humidity) it will be touch dry within 15 minutes and can be recoated within 1 -2 hours. Drying times will vary depending on film thickness, ventilation and weather conditions.

Clean Up and Thinning

Mineral turpentine for brushing and rolling and fast dry thinners for spraying.

Coverage

12 square metres per litre.

Pack Size

1 and 4 , 10 litres

Colours Black, white, safety yellow, red and blue and customer specifications.

Revised January 2021