

Vipond's Paints Pty Ltd

58 Barrie Road, Tullamarine VIC 3043 Phone (03)9350 4188 Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

STRIPPABLE COATING

Description

Vipond's Strippable Coating is a clear water thinned paint that when applied to a nonporous surface (eg glass, metal, plastic, vinyl etc) and allowed to dry, it can be peeled off without affecting the surface.

Use

It can be used to mask surfaces prior to painting or as a coating to protect surfaces against scratching, staining or marking. Not for long term exterior use outside unless overcoated with an exterior paint.

Surface Preparation

Ensure the surface is dry and free of dirt, grease and oil.

Application

Thoroughly stir and apply with brush, roller or spray. It is important to apply a thick coating (approximately 2 - 3 mm wet coat) to allow easy removal. Apply one heavy coat or two medium coats. It is an interior product because of poor water resistance. A topcoat can be applied to improve water resistance for exterior use.

Drying

Under normal drying conditions (above 15°C) it will be touch dry within 1 hour and through dry in 4 hours. Drying times are dependent on the film thickness and drying conditions.

Coverage

Approximately 5 square metres per litre

Clean up

Thin and clean equipment with water.

Re issued January 2021