



Vipond's Paints Pty Ltd
58 Barrie Road Tullamarine , VIC , 3043
Phone (03) 93504 188
Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

TAUTFLEX UNDERCOAT

Description

TautFlex Undercoat is an easy sand, water based undercoat for rigid surfaces before applying TautFlex. It has been introduced to allow the use of TautFlex onto a variety of rigid surfaces. It dries quickly and has excellent filling and sanding properties. Suitable for interior and exterior use.

Use

As an undercoat for TautFlex on a variety of surfaces such as MDF, customwood, timber, plasterboard, colourbond, rigid fibreglass and most primed surfaces. It is particularly useful when the substrate needs filling and sanding or when the adhesion of TautFlex is suspect.

Do not use on flexible surfaces.

Surface Preparation

Ensure the surface is dry and free of dirt, grease or oil.

Application

Stir the paint well then apply with brush, roller or spray. Allow to dry and sand with 240-320 freecut sandpaper. Repeat if a mirror finish is required.

Drying

Under normal drying conditions (above 15°C and low humidity) it will be touch dry within 30 minutes and ready for sanding and topcoating with TautFlex in 2 hours.

Clean Up and Thinning

Thin and clean up with water

Coverage

Approximately 12 square metres per litre per coat.

Pack Size

500ml, 1 litre and 4 litre cans

As the substrates that are used and the methods and conditions of application of this product are beyond control of Vipond's Paints Pty. Ltd. it is recommended that the customer tests the product for their own particular application.

Revised July 2005