



Vipond's Paints Pty Ltd
2 Norris Street North Coburg 3058
Phone (03) 93504188 Fax (03) 93542732
Email info@viponds.com.au

www.viponds.com.au

PRODUCT INFORMATION

TRADITIONAL SIGN ENAMEL

Description

Vipond's Traditional Sign Enamel is a high quality alkyd enamel, featuring a high viscosity resin, durable pigments with the highest concentration to achieve the best possible single brush stroke outcome. Viscosity can be adjusted with thinners, goldsize or linseed oil to achieve the desired flow.

Use

This product can be used on a variety of surfaces including glass, metal, timber, alu panels, colourbond and painted surfaces. On all exterior and interior surfaces.

Surface Preparation

This product can be used on a variety of surfaces.

Best practice is to apply appropriate primers followed by Vipond's Enamel Undercoat, but depending on the job this may not be possible.

Ensure the surfaces are free from dirt, dust, grease and loose or powdery material.

Lightly sand glossy surfaces.

This product is ideal to signwrite onto backgrounds that have been painted with Vipond's Feature Gloss Enamel or Vipond's QD Enamel.

Application

Thoroughly stir the paint and adjust the viscosity with mineral turpentine, TSE Thinners, Goldsize or linseed oil to achieve the desired flow. TSE Thinner will slow the drying in hot weather.

Drying

Under normal drying conditions (15°C and low humidity) it is touch dry within 2 hours and through dry within 24 hours. Recoat after 16 hours.

Cleaning and Thinning

TSE Thinner, Mineral Turpentine

Coverage

Approximately 16 square metres per litre per coat.

Pack Size

White and Black 250 mls, 500 mls, 1 litre and 4 litre
Colours 250ml, 500 ml

May 2016