



PIR Sensor

EM Driver

### PROJECT DETAILS

Project Name	
Fixture Schedule	
Product Number	
Notes	

### KEY FEATURES

- WEATHER-SEALED DIE-CAST ALUMINUM HOUSING
- MOUNTING PLATE IS DESIGNED FOR ANY OVERHEAD INSTALLATION
- POLYCARBONATE OPTICAL LENS PROVIDES WIDE BEAM SPREAD
- BUILT-IN KNOCK OUT SUPPORTS OPTIONAL VERTICAL MOUNT
- OPTIONAL BUILT-IN SENSOR FOR OPTIMUM EFFICIENCY
- OPTIONAL BUILT-IN BATTERY BACKUP
- REPLACES UP TO 250W MH

### KEY SPECIFICATIONS

- **Housing:** Weather-sealed die-cast aluminum
- **Input Voltage:** 120-277Vac & 347-480Vac
- **Operating Temp:** -40°F – 130°F
- **IP:** UL Wet Location Listed
- **PF:** >0.9 Non-Flicker
- **Efficacy:** >140LM/W
- **Dimming:** 1-10V
- **THD:** <20%
- **CRI:** >70

### APPLICATIONS



Parking Garages



Awnings



Canopies



Security Lighting

### CERTIFICATIONS



### MODEL SPECIFICATIONS

Model	Watt	Lumens	Voltage	CCT	LPW	Replaces
LCNP27	27W	3,800LM	120-277V 347-480V	4000K 5000K	140LM/W	100W MH
LCNP40	40W	5,500LM			137LM/W	175W MH
LCNP60	60	8000LM			133LM/W	250W MH

### ORDERING GUIDE

Model Series	Watt (W)	CCT (K) [xx]	Voltage (V)	Finish [y]	Sensor [a]	Remote Controller [b]	Emergency Driver [c]
<b>LCNP   LED Canopy</b>	<b>27   27W</b> <b>40   40W</b> <b>60   60W</b>	<b>40   4000K</b> <b>50   5000K</b>	<b>U   100-277V</b> <b>H   347-480V</b>	<b>D   Dark Bronze *</b> <b>B   Black</b> <b>W   White</b> <b>S   Silver</b>	<b>Blank   None *</b> <b>MS   PIR Motion Sensor</b>	<b>Blank   None *</b> <b>RM   Remote Controller</b>	<b>Blank   None **</b> <b>EM08   EM Driver + 8W Battery</b>

\* Standard option

\*\* Integral Controls & Emergency Drivers

Choose Your Model Specifications Above:

LCNP	27	50	H	D	MS	Blank	EM08
------	----	----	---	---	----	-------	------

**Example Ordering Number:**

**LCNP27-50-HD-MS-EM08**