

Iuxo@RCH

LWPF

30W - 125W LED WALL PACK FIXTURE

COMMERCIAL GRADE

PRODUCT OVERVIEW:

The luxo@RCH LED classic wall pack follows the design traits of the classic metal halide or high-pressure sodium. Engineered to protect against vandalism and even bad weather, these fixtures may be paired with photocells to optimize performance.

Featuring shatter-resistant polycarbonate or glass lens, tamper-proof die-cast aluminum housing and designed to weather extremes, the LWPF-series will exceed lighting demands for driveways, outdoor entry-ways and other general commercial areas.







MODEL SPECIFICATIONS:

Model	Watt (W)	Lumens (LM)	Voltage	CCT (K)
LWPF30	30W	3,600LM	100-277V	4000K 5000K
LWPF40	40W	5,100LM	100-277V 347-480V	4000K 5000K
LWPF60	60W	7,900LM	100-277V 347-480V	4000K 5000K
LWPF90	90W	10,500LM	100-277V 347-480V	4000K 5000K
LWPF125	125W	15,000LM	100-277V 347-480V	4000K 5000K

APPLICATIONS:



PROJECT DETAILS:



KEY FEATURES:

- Weather Resistant, Sealed Die-Cast Aluminum
- Optional Photocell Allows for Security and Optimized Efficiency
- Traditional Metal Halide or High-Pressure Sodium Design
- Mounts Directly to Wall Surface or J-Box
- Thermally Isolated Driver Design
- Replaces Up To 800W MH

UNIVERSAL SPECIFICATIONS:

- Housing: Durable die-cast aluminum
- **Input Voltage:** 120-277Vac or 347-480Vac
- Operating Temp: -40°F 130°F
- IP: UL Wet Location Listed
- PF: >0.9 Non-Flicker
- Efficacy: >115LM/W
- Dimming: 1-10V
- **THD**: <20%
- **CRI**: >70

ORDERING GUIDE:

Model	Watt (W)	CCT (K)	Voltage (V)	Finish (y)	Photocell (a)	Battery Backup (a)	
LWPF LED Wall Pack Fixture	30 30W 40 40W 60 60W 90 90W 125 125W	40 4000K 50 5000K	U 120-277V H 347-480V	B Black D Dark Bronze W White	Blank No Photocell PA 120-277V Photocell	Blank No EM Battery EML EM Battery Backup (15-55VDC) EMH EM Battery Backup (50-180VDC)	
Choose Your Model Specifications Above:							
LWPF	90 90W	50 5000K	U 120-277V	D Dark Bronze	PA 120-277V Photocell	EML EM Battery Backup (15-55VDC)	


Example Ordering Number: LWPF90-50-UD-PA-EML



PRODUCT DIAGRAMS:




PHOTMETRICS:



SIZING/MEASUREMENTS:

Model	Length (in)	Height (in)	Width (in)	Weight (lb)
LWPF30	14.21	9.25	7.20	6.525
LWPF40	14.21	9.25	7.20	6.525
LWPF60	14.21	9.25	7.20	6.724
LWPF90	14.21	9.25	7.20	7.319
LWPF125	14.21	9.25	7.20	8.157





WARRANTY:



(\ 75,000-Hours

The lesser of 7-Years after shipment by Seller, or 75,000-Hours of use.

ARCHIPELAGO will not under any circumstances whether as a result of breach of contract, breach of warranty, tort, strict liability or otherwise be liable for consequential, incidental, special or exemplary damages including but not limited to, loss of pro its or revenues, loss of use of the above product or any other goods or associated equipment or damage to any associated equipment, cost of capital, cost of substituted products, facilities of services, downtime cost, or claims of claimant's customers. ARCHIPELAGO's liability on any claim of any kind for any loss or damages arising out of, resulting from or concerning any aspect of this agreement of from the product or services furnished hereunder shall not exceed the price of the specific product or products listed above which gives rise to the claim. This warranty gives the claimant specific legal rights. The claimant may also have other rights, which vary from state to state.

For a complete documentation of ARCHIPELAGO Lighting, Inc. warranty and limitation of liability, please refer to www.archipelagolighting.com.

CERTIFICATIONS:









QUESTIONS?:

Archipelago Lighting, Inc.

4615 State Street, Montclair, CA 91763 www.archipelagolighting.com sales@archipelagolighting.com

ARCHIPELAGO LIGHTING:

Archipelago Lighting, Inc. manufactures commercial and residential lighting products in USA and China. We are a team of passionate lighting professionals whose goal is to modernize the lighting industry through disruptive LED lighting products. We manufacture a wide variety of products to support the growing adoption of energy efficient LED applications.

