



MODEL SPECIFICATIONS

Model	Watt	Lumens	Voltage	CCT	LPW	Replaces
LWPF	30W	3,600LM	120-277V	4000K 5000K	120LM/W	100W MH
LWPF	40W	5,100LM	120-277V 347-480V		128LM/W	175W MH
LWPF	60W	7,900LM	120-277V 347-480V		122LM/W	250W MH
LWPF	90W	10,500LM	120-277V 347-480V		120LM/W	320W MH
LWPF	125W	15,000LM	120-277V 347-480V		120LM/W	400W MH

PROJECT DETAILS

Project Name	
Fixture Schedule	
Product Number	
Notes	

KEY FEATURES

- WEATHER-SEALED DIE-CAST ALUMINUM HOUSING
- MOUNTING PLATE IS DESIGNED FOR ANY OVERHEAD INSTALLATION
- POLYCARBONATE OPTICAL LENS PROVIDES WIDE BEAM SPREAD
- BUILT-IN KNOCK OUT SUPPORTS OPTIONAL VERTICAL MOUNT
- OPTIONAL BUILT-IN SENSOR FOR OPTIMUM EFFICIENCY
- OPTIONAL BUILT-IN BATTERY BACKUP
- REPLACES UP TO 400W MH

KEY SPECIFICATIONS

- **Housing:** Weather-sealed die-cast aluminum
- **Input Voltage:** 120-277Vac & 347-480Vac
- **Operating Temp:** -40°F – 130°F
- **IP:** UL Wet Location Listed
- **PF:** >0.9 Non-Flicker
- **Efficacy:** >120LM/W
- **Dimming:** 1-10V
- **THD:** <20%
- **CRI:** >70

APPLICATIONS


 Walkways |
Pathways


Entryways


 Perimeter
Lighting

 Security
Lighting

CERTIFICATIONS



ORDERING GUIDE

Model Series	Watt (W)	CCT (K) [xx]	Voltage (V)	Finish [y]	Photocell[a]	Battery Backup
LWPF LED Classic Wall Pack	30 30W	40 4000K	U 100-277V H 347-480V	D Dark Bronze *	Blank No Photocell PS 120-277V Photocell	Blank None ** EM08 EM Driver + 8W Battery
	40 40W	50 5000K		B Black		
	60 60W		W White			
	90 90W		S Silver			
	125 125W					

* Standard option

** Integral Controls & Emergency Drivers

Choose Your Model Specifications Above:

LWPF	60	50	U	D	PS	EM08
-------------	-----------	-----------	----------	----------	-----------	-------------

Example Ordering Number:
LWPF60-50-UD-PS-EM08