



150W



300W

PROJECT DETAILS

Project Name	
Fixture Schedule	
Product Number	
Notes	

KEY FEATURES

- LOW PROFILE, RUGGED ONE-PIECE DIE CAST ALUMINUM HOUSING
- 3G VIBRATION RATED COMPACT DESIGN MINIMIZES WIND LOAD REQUIREMENTS
- 100,000HR LED LIFESPAN BASED ON IES LM-80 AND TM-21 CALCULATIONS
- DARK SKY CONFORMING OPTICS AVAILABLE IN IES TYPE III, IV, OR V
- SCALABLE LUMEN PACKAGES, REPLACING UP TO 1000W MH
- OPTIONAL PHOTOCELL AND OCCUPANCY SENSORS AVAILABLE

KEY SPECIFICATIONS

- **Housing:** Thermally Conductive Rugged One-Piece Die Cast Aluminum
- **Operating Temp:** -40°F – 115°F
- **Input Voltage:** 120-277Vac
- **IP:** UL Wet Location Listed
- **Pf:** >0.9 Non-Flicker
- **Efficacy:** >125LM/W
- **Dimming:** 1-10V
- **THD:** <20%
- **CRI:** >70

MODEL SPECIFICATIONS

Model	Watt	Lumens	Voltage	CCT	LPW	Replaces
LSBX150	150W	19,000LM	100-277V	4000K 5000K	126LM/W	400W MH
LSBX300	300W	38,200LM			125LM/W	1000W MH

ORDERING GUIDE

Model Series	Watt (W)	CCT (K)	Voltage (V)	Mount
LSBX LED Shoebox	150 150W 300 300W	40 4000K 50 5000K	1 120-277V H 200-480V	Blank None * A Slip-Fitter B Square/Round-Pole

* Default option

Choose Your Model Specifications Above:

LSBX	150	50	H	Blank
-------------	------------	-----------	----------	--------------

Example Ordering Number: LSBX150-50-1 (H)
APPLICATIONS


Parking Lots



Facade Lighting



Roadways



General Public

CERTIFICATIONS
