




We make building easy! ©

Building With Polycarbonate 101

Presented by The Polycarbonate Store

A division of Charley's Greenhouse & Garden



Multi-Wall Polycarbonate

- Insulated for lower heating cost
- Nearly unbreakable
- Diffused, even light
- More stable interior climate
- Easy to handle
- Lightweight
- 15-20 year life

Types of Polycarbonate

- | | |
|---------|----------------------------|
| CLEAR | highest light transmission |
| BRONZE | shading and privacy |
| COLORS: | BLUE Accent |
| | GREEN Accent |
| | OPAL Privacy |

Glazing Choices

RECOMMENDATIONS



3 mm

- **3 mm (1/8") Clear tempered safety glass**
Heavy, but has longest life and best clarity. Requires summer shading to protect plants.



6 mm

- **B1274 6 mm (1/4") TwinWall Polycarbonate**
Our standard glazing panel. Very strong and flexible. (R 1.6) Use to replace single glass panes.



10 mm TwinWall

- **B1278 10 mm (3/8") TwinWall Polycarbonate**
Best price for 10 mm. More strength than 6 mm. (R 2.0)




10 mm 3-Wall

- **B1290 10 mm (3/8") 3-Wall Polycarbonate**
Better insulation and clarity than 4 mm or 6 mm. (R 2.1)



16 mm

- **B1283 16 mm (5/8") TripleWall Polycarbonate**
Best clarity and appearance because of the wider flute spacing. Better insulation value (R 2.5).




16 mm

- **B1376 16 mm (5/8") Super 5-Wall Storm Polycarbonate**
Highest strength and insulation value (R 2.78). Best for cold and windy climates.

also available: 25 mm (1") (R = 2.94)

1. Avoid horizontal joints if possible. Panels can be ordered in lengths up to 24 ft.
2. Lay out framework 24½" On Center for 24" wide panels, or 48½" On Center for 48" panels. This will allow 1/2" space between panels for screws and for panel expansion in warm weather.



Polycarbonate 101

Framing Materials


A. WOOD

B. PVC PIPE

C. ALUMINUM & STEEL

D. FASTENERS – Decking screws, lag bolts, washer head screws



E. SILICONE – Sikasil-N Plus Silicone Sealant



Charley's Greenhouse Tips


Building With MultiWall

1. Apply 1/16" Glazing Tape (#B7521) to framework. Install multi-wall panels on tape.
2. For roof only, seal between panels and framework with Foilastic Tape B7550
3. Install Aluminum Bar Caps



Disclaimer:
 These sketches are only intended to show possible framing techniques. They are not structurally engineered or specifically approved by any building code. Structures over 120 sq. ft (sometimes less) often require a building permit.

Greenhouse Design



Framing Ideas




Figure D11




Figure D10

Figure F1





Figure F5



Cutting Multi-Wall Polycarbonate

► 4 mm, 6 mm, 8 mm and 10 mm Polycarbonate

You can cut small amounts with a box knife. Larger jobs should be cut with a circular saw, table saw or saber saw. In all cases, a fine-tooth blade is required. (Plywood/finish blade for circular saw / table saw, and a metal cutting blade for a saber saw.)

Circular Saw / Saber Saw: Clamp a straight-edge to the panel to guide the saw. Proper cutting speed is important ... Too slow and the plastic will melt, too fast and you may have large chips.

Table Saw: Push through the saw as you would a piece of plywood paneling.

Box Knife – Not recommended, but can be used for small, short cuts. Always draw the knife away from the hand holding the polycarbonate sheet. A box knife tends to drag and skip, making it dangerous to use. Draw the knife lightly to start the cut then repeat with more pressure. When the cut is almost complete, you can flex and snap the pieces to finish the separation.

► 16 mm and 25 mm Polycarbonate

Cutting 16 mm and 25 mm Polycarbonate: A table saw and circular saw are the best cutting tools. A saber saw may be useful for cutting holes or custom shapes.

NOTE: When the panels are cut to size, small particles may have entered the flute channels. Compressed air is used to clear the flutes. Peel off the protective film from the inside of the panel and inspect the panel closely. Remove any remaining particles with a vacuum or compressed air. Do not flush the flutes with water because it may take a long time to dry out.

Installing Multi-Wall Polycarbonate

- The framing for Multi-Wall should be 24" to 24½" on center. Cross blocking should be 4 ft. to 6 ft. apart going up rafters between Ridge and Eave, and also in walls over 6 ft. tall.
- Inspect the panels and read any information printed on the protective film.
- Multi-Wall has film on both sides. One side is clear and the other will have printing on it or will be blue. The side with printing, or blue (if there is no printing), is the UV-protected side, which must face outward.
- Verify that any silicone or caulk that will come into contact with the polycarbonate is compatible with the polycarbonate. (Never apply silicone sealant so that it will enter the poly channels of the Multi-Wall.)

CAUTION! The Multi-Wall Panels must be stored in a cool, dry location.

- Do not store in the sun, or the temporary protective film will be difficult or impossible to remove.
- Leave film on one side until after installation is complete (UV side must face out), or mark one side (Fig 4.)

Step 1. Taping the ends of the panels or installing End Caps.

The ends of the polycarbonate panels should be protected to keep out dust and insects. This is done with a special breathable tape (B7524), aluminum channel, or by fitting the panel into a Polycarbonate End Cap. Apply tape to the end of any panel that does not fit into wood channel, aluminum or Poly End Cap. Cover tape with flashing or wood to prevent the sun from drying out the adhesive.


Do not use silicone or caulking to seal the ends of the panels. This would void the warranty.

A. To seal the top ends with the breathable polycarbonate tape:

- Lay out the Multi-Wall panel on a flat surface.
- Peel back plastic film on each side of the panel about 4" to 6" from edge (**fig 1**).
- Measure panel width and cut polycarbonate tape to length.
- Peel off protective backing on tape.
- With one end of tape in each hand, start one end with 1/4" to 3/8" overlap onto panel. Pulling tight with opposite hand, press other end in place (**fig 2**).
- Using fingers, press tape evenly, and then fold onto back side and smooth out (**fig 3**).




Mark "outside" of panel



NOTE: Only remove the protective film from the *inside* of the panels before installation. Peel back the outside protective film about 4" from the edge, but leave the outside film on the panel until after installation is complete. It is difficult or impossible to tell the inside from the outside once both films have been removed. Place a small mark on the outside edge of the panel with a permanent marker (**fig 4**).

B. To enclose the ends with the End Cap (**fig 5**)

- Lay out the Multi-Wall panel on flat surface.
- Peel back plastic film on each side of panel about 4"-6" from edge.
- With the **wider side down**, fit the **End Cap** halfway onto the panel.
- Apply silicone sealant. Then finish pushing the End Cap into place, leaving a small air gap (1/16"-1/8") at the bottom.




* ALTERNATE INSTALLATION OF FOAM GLAZING TAPE (B7521)

Sometimes it will be easier to install polycarbonate panels if the Foam Glazing Tape is on the wood frame, instead of the panels. In **wet** weather, installing the foam tape onto the panels works best over getting it to stick to wet wood. In **dry** weather, or if you build your walls indoors, you can install tape onto the wood frame.

Positioning the panels into place (without using the "misting" method): Leave the foam tape backing on with an inch or so started to help you to position the panels before removing the rest of the backing.

The photos below demonstrate. You can do a whole wall and position the panels before removing the tape backing - then press the panels into place.






Whether installing foam glazing tape directly to the panel or directly to the dry wood frame, **the foam tape adheres to the INSIDE face of the polycarbonate panels.**

Outside face is the UV-protected side that faces the sun.

Step 2. Polycarbonate Installation:



Option 1. Using wood cap Make from 5/4 x 4 decking (net 1" x 3½).

- A. Refer to Step 1A to seal ends with polycarbonate tape.
- B. For installation where two panels will be joined side by side (**fig 6**):
 - a. Lay down two strips of foam glazing tape (B7521), one on each edge of the framing, or on each edge of poly panel.
 - b. Lay the two pieces of polycarbonate down – leave about a 1/4" to 1/2" gap between the panels for expansion and for the screws. Leave the foam tape backing on with an inch or so started to help you to position the panels before removing the rest of the backing and pressing the panels into place.
 - c. Seal with a layer of Foilastic Tape (B7550) for roof applications (**optional**).
 - d. Lay down another two strips of foam glazing tape on the back of the wood cap. Remove backing film.
 - e. Set the wood cap onto panel and attach with coated decking screws every 9" to 12". Screws must be long enough to penetrate 1" into frame.
 - f. Seal screw heads with silicone.
- C. On framing where the rafter is in the middle of the panel (**fig 6.5**):
 - OPTION A: For up to 8 ft. panels, use 1 or 2 screws placed in the center of the panel (**fig 10**). For 12 ft. panels, use 2 screws, one 4 ft. in from each end.
 - OPTION B: Follow procedure with wood cap shown in **fig. 6.5**
- D. For the top and sides where the panels will end (**fig 8**):
 - a. Lay down one strip of foam glazing tape, and remove backing film.
 - b. Set panel in place.
 - c. Place a wood spacer at the end and seal the seam with the Foilastic Tape.
 - d. Lay down another strip of glazing tape.
 - e. Install wood cap with coated decking screws every 9" to 12".
 - f. Seal screw heads with silicone.
- E. Ridge – rip 5/4x6 decking board to make cap (**fig 12.5**).



Option 2. Using Polycarbonate Capping

- A. On framing where 2 panels will be joined (**fig 9**):
 - a. With the **wider side of the Joiner Cap on the bottom**, slip polycarbonate panels into each side of the **Joiner Cap**. Start at one end and slide panels until edge is completely covered by Joiner Cap.
 - b. Set **Joiner Cap** on framing and attach using Washer Head Screws (B7406) every 12" and at each end.
- B. On framing where one panel crosses the framing and does not join another panel (**fig 10**):
 - a. Lay down two strips of foam glazing tape.
 - b. Lay down the panel.
 - c. Add a 1" gasket washer to your Washer Head Screw. This will spread the pressure over a larger area to prevent crushing the polycarbonate.
 - d. For up to 8 ft. panels, use 1 or 2 screws placed in the center of the panel. For 12 ft. panels, use two screws, one 4 ft. in from each end.
- C. For the sides where the panels will end (**fig 11**):
 - a. With the wider side down, fit the **Side Cap** ("F" extrusion) over one side of the Multi-Wall panel.
 - b. Attach using Washer Head Screws every 12".



Option 2. Using Polycarbonate Capping (continued)

D. Poly Ridge Cap (fig 12)

- a. Fasten the Ridge Cap to the ridge beam with truss-head or decking screws. 10 mm Ridge Cap can be used with 6 mm, 8 mm or 10 mm panels.
- b. Insert the polycarbonate into the Ridge Cap.
- c. Leave 1/8" gap at the top to allow the panels to breathe and to expand in warm weather.




Fig 12

- d. **Optional Metal Flashing** should be installed as shown in **Fig. 12.5**




Fig 12.5

Option 3. Using Aluminum Bar Cap

- A. Refer to Step 1. A. to seal ends with polycarbonate tape.
- B. For framing with two panels (**fig 13**):
 - a. Lay down two strips of glazing tape, one for each panel on the edges of the framing. Remove plastic backing tape. (**TIP:** Apply mist to tape from a spray bottle to reduce tack. This allows repositioning, if necessary.)
 - b. Lay the two pieces of polycarbonate down – leave about a 1/4" to 1/2" gap between the panels for expansion and for the screws.
 - c. Slide the rubber gasket into each side of the Aluminum Base.
 - d. Set the Aluminum Base onto the polycarbonate and attach with truss-head screws every 9". Screws must be long enough to penetrate frame 1".
 - e. Slide Aluminum Cap into the base. Crimp end to keep cap in place.
- C. On framing where rafter is in the middle of the panel (**fig 13.5**):
 - a. Lay down two strips of glazing tape.
 - b. Lay down the panel.
 - c. Slide the rubber gasket into each side of the Aluminum Base.
 - d. Set the Aluminum Base onto the polycarbonate and attach with a truss-head screw at each end and every 24".
 - e. Slide Aluminum Cap into the base.
- D. For the sides where the panels will end (**fig 14**):
 - a. Lay down one strip of glazing tape.
 - b. Set panel in place.
 - c. Install a wood spacer at the end.
 - d. Slide the rubber gasket into each side of the Aluminum Base.
 - e. Set the Aluminum Base onto the polycarbonate and attach with truss-head screws every 9" to 12".
 - f. Slide Aluminum Cap into the base. Crimp ends to hold the Aluminum Cap in place.




Fig 13




Fig 13.5




Fig 14

ABOUT B7521

Foam Glazing Tape

1/16" thick x 3/8" W x 150 ft roll

Use when securing panels directly to wood frame. Leave blue backing ribbon on with an inch or so started to help you position the panels before removing the rest of the backing and pressing the panels into place.

- Not needed where there is a polycarbonate joiner cap or side cap.
- Use with Aluminum Bar Caps.



installing wood caps



metal flashing along ridge



1/16" bead of silicone sealant where panel meets the end cap

Sealing

Sikasil-N Plus Silicone Sealant

After the panels are installed seal with a thin bead (1/16" diam. to 1/8" diam) of silicone sealant where the panels fit into the Poly End Capping.

Apply silicone by pushing nozzle over the silicone bead. Pictured application started on worker's right and is moving to his left.




TIPS: Polycarbonate Capping and Aluminum Bar Cap



Aluminum Bar Caps (B1456)

Use these maintenance-free glazing caps to secure glass or polycarbonate (multi-wall) to supporting framework. Includes rubber gasket that seals out moisture. Fasten with screws (not included) every 9 inches. Channel cover hides screws to give a finished, professional appearance. Dark Brown finish. Caps are 2" wide. Glazing Tape #B7521 recommended on framework, under the glazing.



Polycarbonate Capping Systems

Adding polycarbonate to your framework is easier when using these special pieces to hold the panels in place. The Caps are made of a tough, sunlight resistant UVI poly-carbonate, and are weatherproof and maintenance-free. Use End Caps on the top and bottom of polycarbonate to close the channels. This keeps out dirt and insects. Also use End Caps on the outside edge of corner panels.

Always install Joiner and End Caps wide side down.

Builder's Note: Caps are easily cut to length with a hacksaw.



We make building easy! ©

The Polycarbonate Store

A DIVISION OF *Charley's* GREENHOUSE & GARDEN

Your Project Materials List

Polycarbonate Checklist

Thickness	Color	Size	Qty
<input type="checkbox"/> 4 mm TwinWall	<input type="checkbox"/> Clear	4x8	_____
<input type="checkbox"/> 6 mm TwinWall	<input type="checkbox"/> Bronze	4x10	_____
<input type="checkbox"/> 8 mm TwinWall	<input type="checkbox"/> Opal	4x12	_____
<input type="checkbox"/> 10 mm TwinWall		4x14	_____
<input type="checkbox"/> 10 mm 3-Wall		4x16	_____
<input type="checkbox"/> 16 mm 3-Wall		_____	_____
<input type="checkbox"/> 16 mm 5X-Wall		_____	_____
<input type="checkbox"/> 25 mm 3-Wall		_____	_____

Will Call Orders:

Plan ahead on how you will transport polycarbonate sheets. 12 ft long panels need a minimum of 10 ft of support and adequate tie-downs.

Will Call Hours
Monday-Saturday
9-3:30

Connector Checklist

B1456 Brown Aluminum Bar Cap

Length	Qty
<input type="checkbox"/> 4 ft	_____
<input type="checkbox"/> 6 ft	_____
<input type="checkbox"/> 8 ft	_____
<input type="checkbox"/> 10 ft	_____
<input type="checkbox"/> 12 ft	_____
<input type="checkbox"/> _____	_____

Clear Polycarbonate Joiner Cap ("H"), 8' L, 12' L

Thickness	Qty
<input type="checkbox"/> 6 mm	_____
<input type="checkbox"/> 8 mm	_____
<input type="checkbox"/> 10 mm	_____
<input type="checkbox"/> 16 mm	_____

B1453 Snap Joiner Cap ("H")

Length	Qty	Color
<input type="checkbox"/> 4 ft	_____	<input type="checkbox"/> Clear
<input type="checkbox"/> 6 ft	_____	<input type="checkbox"/> Bronze
<input type="checkbox"/> 8 ft	_____	
<input type="checkbox"/> 12 ft	_____	Fits 6 mm, 8 mm, or 10 mm thick panels.
<input type="checkbox"/> _____	_____	

Clear Polycarbonate End Cap ("U"), 4' L, 6' L, 8' L

Thickness	Qty
<input type="checkbox"/> 6 mm	_____
<input type="checkbox"/> 8 mm	_____
<input type="checkbox"/> 10 mm	_____
<input type="checkbox"/> 16 mm	_____
<input type="checkbox"/> 25 mm	_____

Clear Polycarbonate Side Cap ("F"), 12 ft L

Thickness	Qty
<input type="checkbox"/> 8-10 mm	_____
<input type="checkbox"/> 16 mm	_____

Clear Polycarbonate Ridge/Corner Cap ("R"), 8' L, 12' L

Thickness	Qty
<input type="checkbox"/> 8-10 mm	_____
<input type="checkbox"/> 16 mm	_____

Accessory Checklist

B7475 Aluminum Bar Cap & Snap Joiner Cap Screws

Length	Pak Qty
<input type="checkbox"/> 1½" L for 6-10 mm	<input type="checkbox"/> 50 pak
<input type="checkbox"/> 2" L for 16, 25 mm	<input type="checkbox"/> 100 pak

B7406 1½" L or B7407 2" L Washer Head Screws

Length	Pak Qty
<input type="checkbox"/> 1½" L for 6-10 mm	<input type="checkbox"/> 50 pak
<input type="checkbox"/> 2" L for 16-25 mm	<input type="checkbox"/> 100 pak

B7436 1" Gasket Washers

Pak Qty
<input type="checkbox"/> 25 pak
<input type="checkbox"/> 50 pak
<input type="checkbox"/> 100 pak

optional **B7413 Magnetic Socket Driver**
(for B7406 and B7407 screws)

SILICONE SEALANT	Qty
<input type="checkbox"/> B7533 Sikasil-N-Plus for polycarbonate	_____
<input type="checkbox"/> B7538 Lexel for glass	_____

TAPES	Qty
<input type="checkbox"/> B7524 1" Breathable Tape for 6-10 mm	_____
<input type="checkbox"/> B7526 1½" Breathable Tape for 16 mm	_____
<input type="checkbox"/> B7521 1/16" thick x 3/8" W x 150 ft roll Foam Glazing Tape	_____
<input type="checkbox"/> B7550 Foilastic Tape, 50 ft roll	_____

(888) 977-POLY (7659) / polycarbonatstore.com


17979 SR 536, Mount Vernon, WA 98273-3269



Manufacturer-Approved Cleaning Procedures for Multi-Wall Polycarbonate, Acrylic & APET

The UV-resistant surface treatment on one side of the polycarbonate sheet significantly improves long-term weatherability. Periodic cleaning using proper procedures and compatible cleaners is recommended to prolong the service life.

For general cleaning, it is recommended that the following instructions and cleaning agents be used. These procedures and cleaners are also recommended for use on the untreated, interior surface of the polycarbonate sheet, and for acrylic and APET plastics.



CLEANING PROCEDURES

1. Rinse sheet with lukewarm water.
2. Wash sheet with a mild soap and lukewarm water.
3. Use a soft cloth or sponge and gently wash with an up and down motion in the same direction as the flutes, as shown in **Fig. 3**.
4. Rinse the cloth or sponge and change the water often.

DO NOT SCRUB or use brushes or squeegees. The coating on polycarbonate sheets is UV-resistant; IT IS NOT A MAR-RESISTANT COATING.

5. Repeat rinse and dry with a soft cloth to prevent water spotting.

Cleaning Agents that have been found to be COMPATIBLE with polycarbonate sheets under laboratory conditions:

Freon T.F.
Joy
Palmolive Liquid
Top Job
VM&P grade Naptha
Windex with Ammonia
Brilliance® Cleaner, Anti-Static Polisher

Cleaning Agents that have been found to be INCOMPATIBLE with polycarbonate sheets under laboratory conditions and should NOT be used:

~~Lysol~~
~~Pinesol~~
~~Butyl Cellosolve~~
~~Isopropanol~~
~~Formula 409~~ **DO NOT USE**

IMPORTANT: If a material is found to be incompatible in a short-term test, it will usually be found to be incompatible in the field. The converse, however, is not always true. Favorable performance is no guarantee that actual end-use conditions have been duplicated. Therefore, these results should be used as a guide only and the products must be tested under actual end-use conditions by the user.

Polycarbonate sheets are treated on one side for protection against UV damage. This treated side must face outward or toward the light source to provide protection for polycarbonate sheet.

© Copyright 2019 Charley's Greenhouse & Garden

Charley's
GREENHOUSE & GARDEN

17979 SR 536 • Mount Vernon, WA 98273
Phone (800) 322-4707 • 360-395-3001

charleysgreenhouse.com