

K700 TRIPOD WITH REAPER RAIL







HEAVY DUTY CONSTRUCTION





LOCKING CANT



LONG RANGE PRECISION



USER FRIENDLY OFFSET GRIP



DIRECT PICATINNY MOUNT





DURABLE FOAM SOFT GRIPS





3-POSITION ANGLE LOCKS





UP TO 25 LBS LOAD WEIGHT



REAPER RAIL

TECHNICAL	SYSTEM	
SPECIFICATIONS	KJ86003	
DIMENSIONS (IN/MM)	6 X 5.5 X 6.5 / 152 X 139 X 165	
MOUNT TYPE	PICATINNY	
RAIL CANT	+ - 11°	
PAN ROTATION ANGLE	360°	
VERTICAL ROTATION ANGLE	87° DOWN, 21° UP	
MOUNTING	3/8" - 16 THREADED HOLE	
MATERIAL	ALUMINUM	
WEIGHT (LBS/GR)	1.97 / 894	

INCLUDES CAMERA THREAD ADAPTER

CHNICAL HEAVY DUTY TRIPOD		K 700	
	CHNICAL	HEAVY DUTY	TRIPOD

TECHNICAL	HEAVY DUTY T	
SPECIFICATIONS	KJ85001	
TRIPOD MATERIAL	ALUMINUM	
MAX OPERATING HEIGHT (IN/MM)	72 / 1829	
MIN OPERATING HEIGHT (IN/MM)	10.75 / 273	
MAX CENTER COLUMN EXTENSION (IN/MM)	14.9 / 380	
FOLDED LENGTH (IN/MM)	27 / 686	
NUMBER OF LEG EXTENSIONS	3	
MAX LOAD (LBS)	25	
LEG LOCK TYPE	Lever Lock	
WEIGHT (LBS/GR)	5.5 / 2495	

INCLUDES K700 AMT TRIPOD TRIPOD CASE CAMERA THREAD ADAPTER