3M Science. Applied to Life.[™]

3M[™] Versaflo[™] Spray Painters' Kit

Technical Data Sheet

Description

The Versaflo[™] Spray Painters' Kit features a lightweight compact and well-balanced M-Series Faceshield and belt worn V-Series Air Regulator that offers integrated respiratory, eye and face protection.

The faceshield and air regulator are easy to use and maintain while helping to provide the wearer with protection from a range of workplace hazards.

Features

- Lightweight Faceshield, with excellent balance and field of view
- Fully-adjustable head suspension for optimal fit and weight distribution
- A deflector allows airflow to be directed for increased comfort and control
- Integrated low pressure warning whistle and silencer that reduces noise level to less than 65 dBA
- Replaceable active carbon filter removes odours
- Can be used with 3M[™] compressed air hoses up to a maximum length of 30 m
- Air Regulator delivering controlled, constant flow of air with locking control knob
- Auxiliary port allows air tools such as paint spray guns to be connected
- Air Regulator can be adjusted on the belt for right and left-handed users
- Accessories include earmuffs, peel-off visor overlay, helmet cover and chin strap
- Easy to maintain
- Spare parts and accessories are quick and easy to replace

Standards

- High impact visor meets the performance standard of AS/NZS 1337.
- Meets AS/NZS 1716 performance standard for respiratory protection.
- The compressed air supply must comply with the quality requirements of AS/NZS 1715.



ALVM-206E

Operation/Cleaning

Users need to be trained in the safe operation of this equipment. Routine checks must be carried out in accordance with the user instructions. Cleaning should also only be carried out as specified in the user instructions.

Specifications

versario oprași aliters tat		
Pressure range	3.5 – 8 bar	
Maximum pressure	10 bar	
Manufacturer's Minimum Design Flow (MMDF)	170 l/min	
Maximum Flow	305 l/min	
Storage conditions	-10°C to +50°C < 90 %RH	
Operating temperature	-5°C to +40°C and <90% humidity	
Weight	514 g	
Inlet and auxiliary outlet port	¼ inch BSP thread	
Silicone free headtop and air regulator.		
Airline couplings are CEJN fittings.		

Ordering Information

3M Code	Model #	Description
902-03-84	ALMV-206E	Versaflo [™] Spray Painters Kit, ALMV-206E Kit includes: M-206 Faceshield, V-500E Air Regulator, Breathing Tube, tote bin and User Instructions

Spare Parts & Accessories

3M Code	Model #	Description
70071564416	M-976	Versaflo™ Head, Neck & Shoulder Cape 1/Case
52000018318	M-957	Versaflo [™] Forehead Comfort Pad 1/Case
70071564333	M-927	Versaflo [™] Chemical and Scratch Resistant Visor 1/Case
70071564341	M-928	Versaflo [™] Peel-Off Visor Covers 40/Case
70071564366	M-936	Versaflo [™] Comfort Faceseal 5/Case
XA007702583	H31P3AF	Versaflo [™] Helmet Attach Earmuff 1/Box
52000017831	023-05-51P5	Versaflo [™] V-500E Carbon Filter & O-Ring 1/Box
AT019165714	901-00-56	Breathing Hose 7.5M with CEJN connection 1/Each

Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.

The use of Air Panel is recommended to ensure quality breathable air is delivered to the user.



3M Australia Pty Ltd Personal Safety Division Bldg A, 1 Rivett Road North Ryde NSW 2113 TechAssist Helpline: 1800 024 464 Customer Service: 1300 363 565 Email: techassist@mmm.com Web: www.3M.com/au/ppesafety 3M New Zealand Ltd Personal Safety Division 94 Apollo Drive, Rosedale Auckland 0632 TechAssist Helpline: 0800 364 357 Customer Service: 0800 252 627 Email: techassist@mmm.com Web: www.3M.com/nz/ppesafety

3M and Versaflo are trademarks of 3M Company. Please recycle. Printed in Australia. © 3M 2019. All rights reserved. AV011474440