

### WATER-BASED STONECHIP PROTECTOR

#### DEFINITION

**HIDROTEX** is a water-based stonechip protector. Because it is solvent-free and due to its renewed technology, it is an environmentally friendly product. Therefore it complies with the regulations of most exigent countries.

**HIDROTEX** is applicable to areas which require a good stonechip protection as, once the product is dry, it forms an elastic film, resistant to abrasion.



Because of its thixotropy, **HIDROTEX** is easy to apply due to its smoothness at point of application.

**HIDROTEX** is applicable on epoxy primers, polyurethane fillers, hardened paints and even directly onto sheet protecting it from corrosion. **HIDROTEX** can be covered, after 60 minutes, with any type of bodywork paint.

#### PHYSICAL CHARACTERISTICS



<b>Nature:</b>	Elastomers
<b>Colour:</b>	Grey, black
<b>Specific weight:</b>	1,2 kg/l at 20°C
<b>Yield:</b>	6-7 m <sup>2</sup> /l
<b>VOC:</b>	93 g/l Grey, 94 g/l Black

#### APPLICATION

	 Kg/cm <sup>2</sup>		 cm
	HP	RB1	
Thin textured	2-3	4-5	10-15
Thick textured	1-2	2-3	20-30
Texturated seam	1,5	2,5	3

## DRYING TIMES

The drying depends on the ventilation, the environmental temperature, the relative humidity and the thickness. As a general guide, the product is dry and can be topcoated when the colour of the entire piece has changed.

				JET DRY	
	23°C 60 % R.H. 200 microns	60°C	IR		
HIDROTEX	1h	5'	5'	30'	1h

## REMARKS

In order to facilitate the drying process, apply in well-ventilated areas.  
Do not apply in conditions of relative humidity greater than 80 %.

## EQUIPMENT CLEANING

Use preferably warm water. If the product is dry use acetone.

## SAFETY

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

## STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

## GUARANTEE

In unopened original packaging, one year from manufacturing date.

### SUGGESTION:

To achieve the thickness and width of texture desired, progressively increase the flow of the product.

For any technical information contact with our Customer Attention Service or our Technical Department. **ROBERLO SA declines any responsibility due to an incorrect use of the product.**