



# VT141 EXPRESS

E39

VERSION: 180706  
Page: 1/3

RAPID CLEAR 4:1

## DEFINITION



**VT141 EXPRESS** is a very fast curing, high gloss 2K acrylic clear coat. It is ideal for spot repairs as well as for panel applications and very easy to apply due to its very low viscosity even at low pressures, avoiding an excess of overspray. Once applied, the dust free and ambient drying times are very fast. Due to its characteristics, this product is also quick and easy to be polished.

## PHYSICAL CHARACTERISTICS

<b>Nature:</b>	Acrylic 2K
<b>Color:</b>	Colorless
<b>Specific weight:</b>	0,9 kg/cc 20°C
<b>Viscosity CF/4:</b>	13" at 20°C
<b>Dry film thickness:</b>	50-56 microns 2 coats
<b>Coverage:</b>	9-10 m <sup>2</sup> /l
<b>Solids content:</b>	38 % VT141 Express 40 % Application (100:25 vol)
<b>VOC:</b>	535 g/l Application (100:25 vol) 2004/42/EC - IIB (e)(840)(535)

## AUXILIARY PRODUCTS

CT4	Slow Hardener	S322	Standard thinner
CT5	Standard Hardener	S324	Slow thinner
CT6	Fast Hardener		

			
T° (°C)	Hardener	Hardener	Thinner Optional
< 18	CT6	CT6	S322-S324
18 - 25	CT5-CT6	CT5	S322-S324
> 25	CT5	CT4	S324

# VT141 EXPRESS

RAPID CLEAR 4:1

E39

VERSION: 180706  
Page: 2/3

## SURFACE PREPARATION

Apply **VT141 EXPRESS** on the base coat after the flash off time recommended by the manufacturer.

## MIXING RATIO

VT141 Express					
CT4	100:25:0-5	4 : 1	20°C	2 h	
CT5				13" F/4	2 h
CT6					1,5 h

## APPLICATION METHOD

	1,2-1,4	1,7-2,1	15 - 20		
	1,5-1,7	1,7-2,1	15 - 20	2	3-5'
	1,2-1,4	2	10		

## DRYING TIMES

20° C						50° C		Short wave IR		
									FLASH OFF	FULL BAKE
CT4	15'	1h 15'	1h 45'	3 h	3 h	CT4	15'-20'	BLACK	3'	5'
CT5	10'	1 h	1,5 h	3 h	3 h	CT5	15'-20'	WHITE	4'	6'
CT6	10'	45'	1h 15'	2 h 30'	2 h 30'	CT6	15'-20'			

## REMARKS

Humidity affects clearcoat components so the application equipment should be absolutely dry. Close the hardener container immediately after use. When relative humidity is higher than 70% and/or temperatures lower than +10°C it is recommended to dry at 60°C.

## EQUIPMENT CLEANING

Use a cleaning thinner before the pot life has expired.

## SAFETY

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

## STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

## GUARANTEE

One year in unopened original packaging.

For any technical information contact with our Customer Attention Service or our Technical Department. ROBERLO SA declines any responsibility due to an incorrect use of the product.