

JackJaw[®] 501/502 Series Assembly and Operating Instructions

Assembly Instructions

Step 1: Place contents of box on floor or table. Place handle over riser tube with decal facing up and insert short 1/2" - 22 bolt.



Step 2: Start 1/2"-22 self locking nut on to bolt. Tighten bolt using two 3/4" wrenches.



Step 3: Swing link arms up to handle. Insert the long 3/8"-24 bolt through link arms and handle. Install flat washer on bolt. Start 3/8"-24 locking nut on bolt.



Step 4: Use two 9/16" wrenches to tighten riser bolts and nuts and link arms onto handle.

Note: After nut is tight against washer, then, back off the nut on the link arm bolt one half turn from the washer. Handle should raise and lower freely.



Completed Assembly

Operating Instructions

Basic Stake Pulling

- Step 1:** Lift handle to up position so that jaws are fully open.
Step 2: Place unit so that jaws are on either side of the stake. Figure 1 and 2 below.
Step 3: Place foot on or close to base. Figure 3 below. Push down on handle, clamping on stake and lifting it out of the ground.
Step 4: Repeat motion as necessary until stake is free.



1.



2.



3.

Stake Removal from Tilted Ground

- Step 1:** The central post of the stake puller should be aligned with the sign post/stake that is being removed. If the ground is uneven, use two blocks of wood to level the base of the stake puller so that the central shaft is parallel to the sign post/stake
Step 2-4: Same as Basic Stake pulling.

Tip: In soft conditions or mud, place a short piece (1 to 2 feet in length) of 2 x 6 lumber under the base of the unit. This will spread the force over a larger area, allowing stake removal even in muddy conditions.



Handle Extension: Remove clevis pin in handle, extend inner handle to desired length and replace clevis pin. See below.



JJ0501 handle in normal position



JJ0501 handle in extended position

Caution: Never put your fingers or hands between the jaws, or between the jaws and the post.

Replacement Jaw Set - 2 jaws & hardware Part # CA0006

Construction Accessories, Inc. • Phone 937-429-9089 • Fax 937-427-4653

email: warranty@jackjaw.com • www.jackjaw.com

Printed in U.S.A. • Product Made in the U.S.A.

September 2013

JackJaw® 501/502 Operating Instructions



Difficult or Very Tight Stake Removal

If you encounter difficult or very tight stakes, you can optimize the pulling power of the JackJaw by positioning the lever arm perpendicular to the vertical shaft of the stake puller. This maximizes the leverage from the first and most important push on the handle. See Figure 5.

To get this position, follow steps 1-2 to put the stake puller on the stake. Then, gently lift the slide block with your hand from underneath so that the jaws slide up the stake slightly, until the handle is perpendicular. This allows you to get your full weight, safely and comfortably on top of the stake puller handle for the first push. Since the handle is perpendicular, the leverage is maximized in this position.

5.



Pulling Flush Pounded Stakes with the JackJaw502 and AC0009 Adapter

If you pound your stakes so that the heads of the stakes are flush with the surface or flush to a stake bar or frame plate (Figures 6 & 7) you will need an optional stake adapter, AC0009. The JackJaw502 was designed specifically to solve this problem.

Step 1: Slip the AC0009 stake adapter over the head of the stake. See Figure 8.

Step 2: Pull the ring pin at the bottom of the stake puller and extend the base to the high position. Re-insert the pin in the highest hole. Figure 9.

Step 3: Place the metal base of the stake puller as close to the stake as possible. When using a stake bar system, put the metal base of the JackJaw on top of the bar. Figure 10.

Step 4: Raise the handle of the stake puller, and put the shaft of the stake adapter between the jaws of the stake puller. Be careful not to put your fingers in between the jaws and the adapter!

Step 5: Let the handle down to close the jaws on the shaft of the stake adapter.

Step 6: Push down on the handle, pulling up on the adapter (and the stake) until 4-5 inches of the stake are exposed. It may take two or three pulls on the adapter. Figure 11.

Step 7: Move the stake adapter to the next stake and repeat Steps 1 - 6 for each of flush pounded stakes that you need to pull. After all stakes have been pulled up to expose 4-5 inches of each stake shaft, go to Step 8.

Step 8: Pull the ring pin from the high position and retract the base to the normal low position. Re-insert the pin in the lowest hole. Figure 12.

Step 9: Pull all the stakes the rest of the way out using the steps from "Basic Stake Pulling."

6.



7.



8.



9.



10.



11.



12.



VERY IMPORTANT: If you are pulling a stake from a stake bar or frame plate, put the metal base of the JackJaw unit **ON TOP** of the bar or plate. You must pull the stake straight out of the bar or plate. If the unit is on the ground next to the bar or plate, a slight misalignment can cause the stake to bind with the bar, making it difficult to pull from the bar.

Construction Accessories, Inc. • 937-429-9089
email: warranty@jackjaw.com • www.jackjaw.com
Printed in U.S.A. • Product Made in the U.S.A.